

# Vivid 4 is a modular video panel that vividly displays content without the need of bulky media servers. Create dazzling video displays with these lightweight video panels that feature Black body LEDs that accurately reproduce high-contrast videos. Vivid 4 makes a perfect DJ façade and seamlessly integrates with Serato for displaying music videos to add gig excitement.



# videopanels



## Vivid A

Light Source: 21,632 SMD 2020 LEDs (tri-color RGB) 0.3 W, (60 mA), 50,000 hours life expectancy Wavelength: 620 to 625 nm red, 516 to 530 nm green,

460 to 475 nm blue Viewing Angle: 120°

Maximum Illuminance: 1,200 NITS Calibrated Illuminance: 1,000 NITS

Contrast Ratio: 4,300:1 Refresh Rate: 1,920 Hz

**Pixel Density:** 43,264 m2 (104 x 208)

Pixel Pitch: 4.8 mm

Minimum Viewing Distance: 12 ft (4 m)

Control Protocol: Novastar

Power I/O Connectors: Seetronic® powerKON® Signal I/O Connectors: Seetronic® etherKON® Power Linking: 7 units @ 120 V; 13 units @ 230 V

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 280 W, 2.3 A @ 120 V, 60 Hz

Power and Current: 280 W, 1.2 A @ 230 V, 50 Hz

Weight: 27.6 lb (12.5 kg)

**Size:** 19.7 x 1.9 x 39.4 in (500 x 65 x 1000 mm)

Maximum Vertical Hang: 23 panels Maximum Horizontal Hang: 17 panels Required Controllers: Vivid Drive 23N

Optional Mounting Brackets: RB-F50CM, RB-F100CM

Approvals: CE, MET

## Vivid Drive 28N

Control Protocol: Novastar

Control Input Connectors: USB, RJ45

**Video Input Connectors:** HDMI, Display Port, DVI, VGA (x3), CVBS (x2)

55 (XZ)

Video Output Connector: DVI, VGA, RJ45 (x2)

Max. Supported LEDs: 1,310,720

Max. Supported Panels (Vivid 4): 30 per RJ45 Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power and Current:** 42 W, 0.7 A @ 120 V, 60 Hz **Power and Current:** 42 W, 0.4 A @ 230 V, 50 Hz z

Weight: 4.8 lb (2.2 kg)

**Size:** 19 x 12 x 1.7 in (483 x 305 x 44 mm)

Approvals: CE

# The CHAUVET DJ line of Intimidator moving head fixtures is a powerful lighting addition to any large scale event production. Depending on which fixture is in your arsenal, a dynamic combination of bright LEDs, gobo and prism effects, zoom capability and more are at your service to bring your large scale events to life.

## movingheads



## **Intimidator Hybrid 140SR**

DMX Channels: 13 or 19

**Light Source:** Osram Sirius HRI 140 W discharge lamp, 6,000 hours **Zoom Angle:** (motorized) (beam): 3° to 11° (spot): 7° to 21°

(wash): 14° to 28°

**Colors:** 12 + white, split colors, continuous scroll at variable speeds **Gobo wheel (1):** 9 + open, rotating, interchangeable, slot-n-lock,

continuous scroll at variable speeds

Gobo wheel (2): 17 + open, metal, continuous scroll at variable speeds

Illuminance (3° beam): 382,000 lux @ 5 m Illuminance (7° spot): 104,700 lux @ 5 m Illuminance (14° wash): 4,680 lux @ 5 m

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 33.4 lb (15.2 kg)

**Size:** 12.6 x 8.6 x 20.2 in (322 x 220 x 513 mm)

Optional Road Case S35X

114



## **Intimidator Beam 140SR**

DMX Channels: 8 or 14

**Light Source:** Osram Sirius HRI 140 W discharge lamp,

100 hours

Beam Angle (beam): 3° Beam Angle (frost): 21°

Colors: 14 + white, split colors, continuous scroll at variable speeds
Gobos: 17 + open (all aluminum), fixed, continuous scroll at

able speeds

**Prism:** 16-facet round, bidirectional rotation at variable speeds

Illuminance: 382,000 lux @ 5 m Illuminance: 37,900 lux @ 15 m

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Weight:** 25.8 lb (11.7 kg)

**Size:** 12.7 x 8.6 x 16.5 in (322 x 220 x 420 mm)

Optional Road Case S35X



## **Intimidator Spot 475Z**

DMX Channels: 10 or 16

**Light Source:** 1 LED (white) 250 W, (16.3 A), 50,000 hours

Zoom Angle (motorized): 13° to 28°

**Gobos wheel (1):** 7 + open (6 metal + 1 glass), rotating, interchangeable, indexing, continuous scroll at variable speeds **Gobo wheel (2):** 8 + open, continuous scroll at variable speeds

**Colors:** 7 + white, split colors, continuous scroll at variable speeds

Illuminance (13°): 106,300 lux @ 2 m Illuminance (28°): 23,680 lux @ 2 m

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Weight:** 36.2 lb (16.5 kg)

**Size:** 14.3 x 9.8 x 20.9 in (363 x 250 x 531 mm)



## Intimidator Spot 375Z

**DMX Channels:** 9 or 15

**Light Source:** 1 LED (white) 150 W, (12.3 A), 50,000 hours

**Zoom Angle (motorized):** 10° to 23°

**Gobo Wheel:** 7 + open (6 aluminum + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at

riable speeds

Colors: 7 + white, split colors, continuous scroll at variable speeds

Prism (1): 6-facet round, bidirectional rotation at variable speeds

Prism (2): 5-facet linear, bidirectional rotation at variable speeds

Illuminance: (10°): 38,000 lux @ 2 m Illuminance: (23°): 19.850 lux @ 2 m

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 27.2 lb (12.4 kg)

**Size:** 8.6 x 12.7 x 18.3 in (220 x 322 x 466 mm)

Optional Road Case S35X







# Moving light makes events come alive. Give performance spaces a dynamic visual personality with animated razor sharp beams, crisp gobos and bright, colorful textures that only moving head fixtues can provide. Moving lights. Moving people.

# movingheads





## Intimidator Wash Zoom 450

DMX Channels: 14 or 29

Light Source: 12 LEDs (quad-color RGBW) 15 W (3.7 A),

000 hours

Zoom Angle (motorized): 14° to 58° Illuminance: (14°): 25,610 lux @ 2 m Illuminance: (58°): 1,960 lux @ 2 m

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 15.8 lb (7.2 kg)

**Size:** 7.6 x 10.9 x 14.3 in (194 x 277 x 363 mm)

## **Intimidator Spot 360**

DMX Channels: 8 or 14

**Light Source:** 1 LED (white) 100 W, (3.2 A), 50,000 hours

**Zoom Angle (manual):** 12° to 17°

**Gobos:** 7 + open (6 metal + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

**Colors:** 8 + white, split colors, continuous scroll

at variable speeds

**Prism (1):** 3-facet round, bidirectional rotation at variable speeds

**Prism (2):** 5-facet linear, bidirectional rotation at variable speeds

**Illuminance (12°):** 5,470 lux @ 5 m **Illuminance (17°):** 19,710 lux @ 2 m

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 25 lb (11.4 kg)

**Size:** 16.65 x 12.68 x 11.69 in (423 x 322 x 297 mm)

Optional Road Case S35X



## Intimidator Tri

DMX Channels: 15 or 30

Light Source: 6 LEDs (quad-color RGBW) 21 W (6.3 A),

50,000 hours

**Zoom Angle (motorized):** 7° to 53° **Illuminance:** (7°): 16,000 lux @ 2 m **Illuminance:** (53°): 1,350 lux @ 2 m

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 20 lb (9.2 kg)

**Size:**  $10.9 \times 10.9 \times 15.2$  in  $(278 \times 278 \times 386$  mm)

# CHAUVET DJ SlimPAR Pro wash lights provide a bright, powerful punch for maximum event lighting impact and can wash any stage or event space with warm, rich and vibrant colors. With the new addition of D-Fi USB compatibility, SlimPAR Pro fixtures are equipped with wireless DMX capability taking creative lighting flexibility to new heights.

## washfixtures









## SlimPAR Pro W USB

DMX Channels: 3, 4 or 9

 $\textbf{Light Source:}\ 12\ (tri\text{-color CW,WW,A})\ 6\ W\ (1.4\ A),\ 50,000$ 

Beam Angle: 17°

Illuminance: 3,097 lux @ 2 m

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 7 lb (3.2 kg) Size: 10 x 3.9 x 11.4 in (253 x 98 x 290 mm)

## SlimPAR Pro Q USB

DMX Channels: 4, 5 or 10

**Light Source:** 12 (quad-color RGBA) 6 W (2 A), 50,000

Beam Angle: 16°

Illuminance: 5,690 lux @ 2 m

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 7.2 lb (3.3 kg) Size: 10 x 3.9 x 11.4 in (253 x 98 x 290 mm)

## SlimPAR Pro H USB

DMX Channels: 6, 7 or 12

Light Source: 12 (hex-color RGBAW+UV) 10 W (2.4 A),

50,000 hours Beam Angle: 24°

Illuminance: 3,218 lux @ 2 m

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Weight:** 7.2 lb (3.3 kg) **Size:** 10 x 3.9 x 11.4 in (253 x 98 x 290 mm)

# CHAUVET DJ spotlight fixtures are versatile and powerful featuring hard focus, soft washes and crisp, bright beams to project from distances near or far.

# followspotfixtures





## **LED Followspot 75ST**

**DMX Channels:** 3

Light Source: 1 LED (cool white) 75 W (18 A) 50,000 hours Gobo Size: 23.7 mm outside, 21.3 mm image,

1 mm max thickness

Zoom Angle (manual): 14° to 20° Illuminance: (14°): 8,140 lux @ 2 m Illuminance: (20°): 4,650 lux @ 2 m

Input Voltage: 120/230 VAC, 50/60 Hz (switchable)

Weight: 13.3 lb (6 kg)

**Size:** 22 x 10.8 x 11.5 in (560 x 276 x 292 mm)

DMX Channels: 3

Light Source: 1 LED (cool white) 120 W (30.6A),

50,000 hours

Zoom Angle (manual): 14° to 20° **Illuminance:** (14°): 16,060 lux @ 2 m Illuminance: (20°): 7,900 lux @ 2 m


Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 16.6 lb (7.5 kg)

**Size:** 22.9 x 11 x 13.4 in (582 x 279 x 341 mm)

# Atmospheric Fluids CHAUVET DJ has a variety of haze machines, fog machines and atmospheric effects with a full array of powerful production features to meet any event effect needs. Quick Dissipating Fluid High Performance Fog Fluid High Density Fog Fluid High Performance Haze Fluid

## haze & fogmachines



## **Hurricane Haze 4D**

DMX Channels: 2 Tank Capacity: 0.9 gal (3.75 l) Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz Output: 4,300 cfm Weight: 13.2 lb (6 kg)

**Size:** 11 x 15.5. x 9.6 in (277 x 396 x 245 mm)



## Hurricane 1600

DMX Channels: 1 Tank Capacity: 0.63 gal (2.4 l)

Input Voltage: 120 VAC, 60 Hz or 230 V, 50 Hz

Output: 25,000 cfm Weight: 13.2 lb (6 kg)

**Size:** 13.7 x 12.3 x 10 in (348 x 312 x 253 mm)



## **Hurricane 1800 Flex**

DMX Channels: 1 Tank Capacity: 1 gal (3.8 l)

Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz

Output: 25,000 cfm Weight: 19.0 lb (8.7 kg)

**Size:** 20.4 x 11.9 x 10.8 in (518 x 302 x 274 mm)

# Photo by: AJR Create a white fog that hugs the floor and dissipates without rising or blast a dynamic and safe pyrotechnic-like effect without the use of any toxic chemicals.

## haze & fogmachines





## Vimbus

Tank Capacity: 4.5 gal (17 l)

Heat-up time: (single element): 50 min Heat-up time: (dual element): 30 min Reheat time: (single element): 30 min Reheat time: (dual element): 15 min

Average runtime: 6 min

Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz

Dry ice capacity: 10 lb (4.5 kg) Weight (full): 75 lb (34 kg)

**Size:** 20 x 18 x 19 in (513 x 465 x 470 mm)

## Cumulus

Tank Capacity: .9 gal (3.25 l)
Water Tank Capacity: 2 gal (7.6 l)
Heat-up time: 3 min
Output: 10,000 cfm
Fog Fluid Consumption: 80 ml/min

Water Consumption: 930 ml/min

Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz

**Weight:** 58.8 lb (26.7 kg)

**Size:** 25 x 16 x 18 in (625 x 409 x 453 mm)



## Hurricane Bubble Haz

Tank Capacity: 0.21 gal (0.8 l) each Heat-up Time: 3 min Output: 10.000 cfm

Fluid Consumption (haze): 16 ml/min Fluid Consumption (bubble): 22 ml/min

Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz Weight: 20.2 lb (9.2 kg)

**Size:** 12.2 x 12.3 x 15.5 in (310 x 312 x 394 mm) **Compatible Fluids (haze):** HDF, HFG

Compatible Fluids (bubble): BJG

# CHAUVET DJ's battery powered Freedom series fixtures are 100% wireless D-Fi transceiver technology. Bright, dynamic light with a variety of LED color combinations for unlimited color mixing anywhere you need it.

# batterypowered



## Freedom Par Hex-4

**DMX Channels:** 6, 8, or 12

Light Source: 4 LEDs (hex-color RGBAW+UV) 10 W (2 A), 50,000 hours

Beam Angle: 23°

Maximum Run Time: (single color) up to 20 hours

Illuminance: 1,372 lux @ 2 m

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 6.2 lb (2.9 kg)

**Size:** 5.4 x 5.7 x 7.2 in (138 x 145 x 184 mm)



## Freedom Par Quad-4

DMX Channels: 4, 6 or 10

Light Source: 4 LEDs (quad-color RGBA) 5 W (2 A), 50,000 hours

Beam Angle: 15°

Maximum Run Time: (single color) up to 20 hours

Illuminance: 2,300 lux @ 2 m

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 6.2 lb (2.8 kg)

**Size:** 5.4 x 5.7 x 7.2 in (138 x 145 x 184 mm)



## Freedom Flex H4 IP

DMX Channels: 6, 8 or 12

Light Source: 4 LEDs (hex-color RGBAW+UV) 10 W, (2 A), 50,000 hours

Ream Angle: 2

Maximum Run Time: (single color) up to 20 hours

Illuminance: 2,163 lux @ 2 m

Weight: 8.8 lb (4 kg)

**Size:** 5.7 x 5.4 x 8 in (145 x 138 x 204 mm)

# CHAUVET DJ's battery powered Freedom series fixtures are 100% wireless D-Fi transceiver technology. Bright, dynamic light with a variety of LED color combinations for unlimited color mixing anywhere you need it.

# batterypowered









## reedom Centerpiece

**DMX Channels:** 6, 8, 10, 12 or 16

**Light Source (ring 1):** 12 LEDs (quad-color RGBW) 0.2 W (0.018 mA) 50,000 hours

**Light Source (ring 2):** 7 LEDs (quad-color RGBW) 0.2 W (0.018 mA) 50,000 hours

Light Source (ring 3): 20 LEDs (dual-color CW/WW) 0.1 W (0.018 mA) 50,000 hours

**Beam Angle:** 23° **Maximum Run Time (single color):** up to

16 hours

Illuminance: 510 lux @ 1 m

**Weight:** 3 lbs (1.3 kg) **Size:** 9.4 x 9.4 x 1.3 in (237.9 x 237.9 x 32.5 mm)

## Freedom Cyc

**DMX Channels:** 4, 6 or 10

Light Source: 16 LEDs (4 red, 4 green, 4 blue, 4 warm white) 48 W total (3.5 A), 50.000 hours

Beam Angle: 52°

**Maximum Run Time (single color):** up to 20 hours

Illuminance: 418 lux @ 2 m Input Voltage: 100 to 240 VAC, 50/60 Hz

(auto-ranging)

Weight: 7.2 lb (3.3 kg)

**Size:** 7.5 x 5.8 x 5.4 in (191.2 x 148.2 x 138 mm)

## Freedom Q11

DMX Channels: 4, 6 or 10

Light Source: 1 LED (quad-color RGB+WW) 6 W. (2 A), 50.000 hours

Color Temperature (WW LED): 3700 K Beam Angle (w/o filter): 8°

Maximum Run Time (single color): up to 15 hours

Illuminance (w/o filter): 1,700 lux @ 2 m

Input Voltage: 8.4 VDC, 1.3 A (external power supply: 100-240 VAC, 47/63

Hz) Wojak

**Weight:** 1.4 lb (0.6 kg)

**Size:** 3.8 x 3 x 5.5 in (97 x 75 x 139 mm)

## Freedom H

DMX Channels: 6, 8 or 12

Light Source: 1 LED (hex-color RGBAW+UV) 10 W. (3 A), 50,000 hours

Beam Angle: 21°

**Maximum Run Time:** (single color) up to 20 hours

Illuminance (w/o filter): 314 lux @ 2 m Input Voltage: 8.4 VDC, 1.35 A (external power supply: 100-240 VAC, 50/60 Hz)

**Weight:** 1.4 lb (0.7 kg)

**Size:** 3.8 x 3 x 8.5 in (97 x 75 x 139 mm)

# CHAUVET DJ IP-rated fixtures are built rugged to withstand the elements and deliver powerful outdoor lighting options rain or shine.

## outdoorfixtures









## **COLORband PiX IP**

**DMX Channels:** 3, 4, 6, 7, 9, 12, 18 or 36 Light Source: 12 LEDs (tri-color RGB) 3 W (1,050 mA),

50,000 hours

Beam Angle: 20°

Illuminance: 2.325 lux @ 2 m P Rating: IP65

Input Voltage: 100 to 240 VAC, 50/60 Hz

(auto-ranging)

Weight: 13.5 lb (6.1 kg) **Size:** 39 x 3.9 x 6.8 in (993 x 100 x 173

## SlimPANEL Tri 24 IP

DMX Channels: 3, 4, 5 or 9

Light Source: 24 LEDs (tri-color RGB) 3 W. (1,050 mA).

50,000 hours

Beam Angle: 20°

Illuminance: 5.850 lux @ 2 m **IP Rating: IP65** 

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Weight:** 13.8 lb (6.2 kg)

**Size:** 10.5 x 11.9 x 5.3 in (268 x 301 x 134

## Freedom Par Quad-4 IP

DMX Channels: 4, 6 or 10

Light Source: 4 LEDs (quad-color RGBA) 5 W. (2 A), 50,000 hours

Beam Angle: 15°

Illuminance: 2.464 lux @ 2 m

**IP Rating:** IP54

**Input Voltage:** 100 to 240 VAC, 50/60 Hz

(auto-ranging)

Weight: 8.0 lb (3.6 kg)

**Size:** 5.7 x 5.4 x 7.5 in (145 x 138 x 191

## Freedom Flex H4 IP

DMX Channels: 6, 8 or 12

Light Source: 4 LEDs (hex-color RGBAW+UV) 10 W, (2 A), 50,000 hours

Beam Angle: 23°

Maximum Run Time: (single color) up to 20 hours

Illuminance: 2,163 lux @ 2 m

**IP Rating:** IP54

Weight: 8.8 lb (4 kg)

**Size:** 5.7 x 5.4 x 8 in (145 x 138 x 204 mm)

# A new day of production lighting power. Stage-ready fixtures produce powerful warm spots and washes to highlight the action.

## **EVEseries**









## **EVE E-100Z**

DMX Channels: 1 or 3

Light Source: 1 LED (warm white) 100 W

(2.3 A), 50,000 hours **Color Temperature:** 3500 K

Gobo Size: M (66 mm outside, 48 mm image, 2 mm max thickness)
Zoom Angle (manual): 14° to 30°

Illuminance: (14°): 15,100 lux @ 2 m Illuminance: (30°): 3,800 lux @ 2 m Input Voltage: 100 to 240 VAC, 50/60 Hz

(auto-ranging)

Weight: 12.6 lb (5.7 kg)

**Size:** 24 x 7.2 x 16.9 in (611 x 183 x 430 mm)

## **EVE E-50Z**

**DMX Channels:** 1 or 3

Light Source: 1 LED (warm white) 50 W,

MET

(1.3 A), 50,000 hours **Color Temperature:** 3500 K

**Gobo Size:** D (53.3 mm outside, 43 mm image, 2 mm max thickness) **Zoom Angle (manual):** 20° to 39°

Illuminance: (20°): 7,910 lux narrow @ 2 m Illuminance: (39°): 2,710 lux wide @ 2 m Input Voltage: 100 to 240 VAC, 50/60 Hz

(auto-ranging)

Weight: 9.2 lb (4.2 kg)

**Size:** 18.9 x 6.2 x 15 in (480 x 157 x 381 mm)

## **EVE F-50Z**

**DMX Channels:** 1 or 3

Light Source: 1 LED (warm white) 50 W, (1.3 A), 50,000 hours Color Temperature: 3500 K

Zoom Angle (manual): 17° to 50° Illuminance: (17°): 4,780 lux @ 2 m Illuminance: (50°): 998 lux @ 2 m

Input Voltage: 100 to 240 VAC, 50/60 Hz

(auto-ranging)
Weight: 8.4 lb (3.9 kg)

**Size:** 11.1 x 8.3 x 13 in (281 x 212 x 328 mm)

## EVE TF-20

Light Source: 1 COB LED (warm white)

20 W, (0.5 A), 50,000 hours **Color Temperature:** 2700 K

Beam Angle: 24°
Illuminance: 1,506 lux @ 2 m

Input Voltage: 85 to 120 VAC, 50/60 Hz


(auto-ranging)
Weight: 2.6 lb (1.2 kg)

**Size:** 6 x 5.5 x 7.25 in (153.5 x 140 x 184 mm)

# Sometimes the most effective event lighting is a subtle, warm and rich splash of color. The EVE series of wash lights can turn an event space from dull to thrilling. They provide robust and tasteful color palletes that personalize a space and create colorful backgrounds for events.

## **EVEseries**





DMX Channels: 1, 2 or 4
Light Source: 1 COB LED (warm white)
100 W, (2.7 A), 50,000 hours
Color Temperature: 3500 K
Illuminance (25°): 7,920 lux @ 2 m
Illuminance (35°): 4,340 lux @ 2 m
Input Voltage: 100 to 240 VAC,
50/60 Hz (auto-ranging)
Weight: 7.6 lb (3.5 kg)
Size: 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)



## EVE P-130 RGB

DMX Channels: 3 or 9
Light Source: 40 LEDs (13 red, 13 green, 14 blue) 130 W total, (2.5 A), 50,000 hours
Illuminance (25°): 2,190 lux @ 2 m
Illuminance (35°): 1,100 lux @ 2 m
Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
Weight: 7.6 lbs (3.5 kg)
Size: 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)



## **EVE P-140 VW**

DMX Channels: 3 or 9

Light Source: 40 LEDs (13 cool white, 13 warm white, 14 amber) 140 W total, (2.4 A), 50,000 hours

Color Temperature Range: 2700 to 13000 K

Illuminance (25°): 2,490 lux @ 2 m

Illuminance (35°): 1,245 lux @ 2 m

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Weight: 7.6 lbs. (3.5 kg)

Size: 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)



## **EVE P-150 UV**

DMX Channels: 1 or 5
Light Source: 40 LEDs (UV)
150 W total, (2 A), 50,000 hours
Coverage Angle (narrow lens): 25°
Coverage Angle (no lens): 35°
Input Voltage: 100 to 240 VAC,
50/60 Hz (auto-ranging)
Weight: 7.6 lbs (3.5 kg)
Size: 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)



## **GLOBAL HEADQUARTERS**

5200 NW 108th Avenue Sunrise, FL 33351 USA

7555 N. San Fernando Road Burbank, CA 91505 USA

MEXICO BRANCH Av. de las Partidas 34 - 3B (entrada por Calle 2) Zona Industrial Lerma Lerma, Edo. de México, CP 52000 México

## **EUROPEAN OFFICES**

Stokstraat 18 9770 Kruishoutem Belgium

## FRANCE BRANCH

3, rue Ampère 91380 Chilly Mazarin France

GERMANY BRANCH Bruno-Burgel-Str. 11 DE-28759 Bremen Germany

## **UK BRANCH**

Unit 1C Brookhill Road Industrial Estate Pinxton, Nottingham NG16 6NT **United Kingdom** 



