



Beamer 6 FX

Beamer 6 FX is a multi-effect light that includes adjustable RGBW beams, a round SMD strobe and a red/green pattern laser that produces thousands of razor sharp beams. Large room coverage is possible by positioning each of the 6 RGBW beams independently. The ultra-bright LED strobe ring with built-in motion effects creates dynamic lightshows. Beamer 6 FX features flexible control options including automated and sound-activated programs, master/slave, DMX or an optional [IRC-6](#) remote. Save time running cables and extension cords by power linking multiple units.



Highlights

- A multi-effect light that includes adjustable RGBW beams, a round SMD strobe and a red/green pattern laser
- Red and green laser produces thousands of razor sharp beams that cover a large area
- Achieve maximum room coverage by positioning each of the 6 RGBW beams independently
- Create energy with the ultra-bright LED strobe ring with built-in motion effects
- Flexible control using automated and sound-activated programs, Master/Slave, DMX or an optional IRC-6
- Save time running cables and extension cords by power linking multiple units

Specifications

- DMX Channels: 2 or 15
- DMX Connectors: 3-pin XLR
- Light Source: (Beam): 6 LEDs (RGBW) 5 W, (2 A), 50,000 hours life expectancy
(Strobe): 24 LEDs (White) 0.3 W, (0.1 A), 50,000 hours life expectancy
(Lasers): 650 nm/100 mW (Red) laser diode, 532 nm/30 mW (Green) laser diode
- Strobe Rate: (Beam): 1 to 20 Hz
(Strobe): 1 to 20 Hz
- Beam Angle: 3°
- Power Linking: 12 units @ 120 V; 22 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 41 W, 0.6 A @ 120 V, 60 Hz
40 W, 0.3 A @ 230 V, 50 Hz
- Weight: 6.2 lb (2.9 kg)
- Size: 15.3 x 15.3 x 11.2 in (390 x 390 x 285 mm)
- Approvals: CE, FDA
- Optional Controllers: IRC-6

What's Included

- Power Cord
- Hanging bracket with mounting hardware