




COLORband PiX USB

COLORband PiX USB is a linear LED wash light that functions as a pixel mapping effect, blinder or wall washer. It features [D-Fi USB](#) compatibility for wireless Master/Slave or DMX control. Pixel mapping functions mean you can create amazing animations and video effects. Access to multiple pre-built programs is available with or without DMX. The fixture's high-power, tri-color LEDs nearly eliminate multicolor shadows and its high-frequency LED dimming lets you achieve flicker-free operation suitable for video applications. Save time running cables and power cords by power linking multiple units. ColorBand PiX USB is ideal for quiet applications due to its silent operation and no moving parts. Control of static colors and automated programs is easy with the optional [IRC-6 remote](#). Fits best in the optional [CHS-60 VIP Gear Bag](#).



Highlights

- Full-size LED strip light functions as a pixel mapping effect, blinder or wall washer
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Create amazing animations and video effects with individual LED control
- Convenient access to multiple pre-built programs with or without DMX
- Easily generate complex shows with ShowXpress Pixels
- Includes multiple DMX personalities for a wide variety of programming styles
- Nearly eliminate multicolor shadows with high-power, tri-color LEDs
- Achieve flicker-free video operation with high-frequency LED dimming
- Save time running cables and power cords by power linking multiple units
- Ideal for quiet applications due to silent operation and no moving parts
- Point-and-shoot operation of static colors and automated programs with the optional IRC-6 remote
- Easily transports in the optional CHS-60 VIP Gear Bag

Specifications

- DMX Channels: 3, 4, 6, 7, 8, 9, 12, 18, 36 or 41
- DMX Connectors: 3-pin XLR
- Light Source: 12 LEDs (tri-color RGB) 3 W (1,000 mA), 50,000 hours life expectancy
- Strobe Rate: 0 to 24.5 Hz
- PWM Frequency: 1.22 kHz
- Beam Angle: 27°
- Field Angle: 45°
- Illuminance: 2,245 lux @ 2 m
- Power Linking: 11 units @ 120 V; 21 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 50 W, 0.7 A @ 120 V, 60 Hz 47 W, 0.4 A @ 230 V, 50 Hz
- Weight: 4 lb (1.8 kg)
- Size: 38.9 x 2 x 6.2 in (987 x 49 x 157 mm)
- Approvals: CE, MET
- Optional Controllers: IRC-6, D-Fi USB

What's Included

- Power cord
- Hanging bracket with mounting hardware
- Warranty card
- Quick Reference Guide