



COREbar 4

COREbar 4 is a complete, all-in-one wash lighting solution designed for mobile entertainers. It produces a full spectrum of light with unsurpassed color mixing using chip-on-Board (COB) technology. Achieve total room or stage coverage with four individually adjustable heads and easily set up and tear down in minutes using the included tripod, footswitch and carry bags. For the ultimate light show, mount up to four additional fixtures to the top of the fixture using built-in power outlets and maximize setup possibilities and configurations with two included L-brackets. Or for large, coordinated light shows, pair COREbar 4 with other 4BAR fixtures. Achieve flicker-free video operation with high-frequency LED dimming and easily control the fixture using the included footswitch or standalone or DMX mode.



Highlights

- Complete wash lighting solution designed for mobile entertainers
- Produce a full spectrum of light with robust color mixing using Chip-on-Board (COB) LEDs; COB LEDs produce unsurpassed color mixing from a single-point light source
- Achieve total room or stage coverage with 4 individually adjustable heads
- Easily set up and tear down in minutes using the included tripod, footswitch and carry bags
- Create the ultimate light show by mounting up to 4 additional fixtures to the top of the COREbar™ 4
- Provide electricity to additional lights by using built-in power outlets
- Maximize setup possibilities and configurations with 2 included L-brackets
- Multiple control options with the included footswitch or standalone and DMX capabilities
- Create large, coordinated light shows with other 4BAR™ products
- Achieve flicker-free video operation with high-frequency LED dimming



Maximize setup possibilities and configurations with 2 included L-brackets

Specifications

- DMX Channels: 3 or 15
- DMX Connectors: 3-pin XLR
- Light Source: 4 LEDs (tri-color RGB) 17 W (2 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 17 Hz
- PWM Frequency: 90.3 KHz
- Beam Angle: 31°
- Field Angle: 42°
- Illuminance: 283 lux @ 2 m (per pod)
- Power Linking: 8 units @ 120 V; 16 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 109 W, 0.9 A @ 120 V, 60 Hz 116 W, 0.5 A @ 230 V, 50 Hz
- Weight: 8.8 lb (4 kg)
- Size: 29.5 x 5.3 x 11.2 in (749 x 135 x 285 mm)
- Approvals: CE
- Stand Height: 4.7 to 7.6 ft (1.4 to 2.3) m

What's Included