



## EVE F-50Z

EVE F-50Z is an LED Fresnel fixture that shines a soft-edged, warm white spot and features [D-Fi™ USB](#) compatibility for wireless master/slave or DMX control. It's designed for mobile and installation applications. Manual zoom gives you the flexibility to project from any distance. You can operate EVE F-50Z in standalone mode eliminating the need for DMX control and you can save time running extension cords by power linking multiple units.



# Highlights

- Stylish, compact Fresnel perfect for small to medium stages and theatres
- Warm white LED with high CRI show the true natural colors of scenery and cast
- Flexibility to project from any distance using the manual zoom
- D-Fi™ USB compatibility for wireless Master/Slave or DMX control
- powerCON®-compatible power input/output connections for power linking
- Included Barn Doors keeps light where you need it
- Included Gel Frame adds a splash of color to any scene

## Specifications

- DMX Channels: 1 or 3
- DMX Connectors: 3-pin XLR
- Light Source: 1 LED (warm white) 50 W, (1.3 A), 50,000 hours life expectancy
- Beam Angle: (Narrow): 17°  
(Wide): 50°
- Illuminance: (17°): 4,780 lux @ 2 m  
(50°): 998 lux @ 2 m  
(17°): 853 lux @ 5 m  
(50°): 156 lux @ 5 m
- Power Linking: 16 units @ 120 V; 26 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 60 W, .5 A @ 120 V, 60 Hz  
58 W, .3 A @ 230 V, 50 Hz
- Zoom Angle: (manual): 17° to 50°
- Weight: 8.41 lb (3.9 kg)
- Size: 11.1 x 8.3 x 13 in (281 x 212 x 328 mm)
- Approvals: CE, MET
- Accessory Holder/Gel Frame Size: 6.25 in (158 mm)
- Color Temperature: 3500 K
- CRI: 92
- Bracket Mounting Hole: M12
- Optional Controllers: D-Fi USB

## What's Included

- EVE F-50Z
- Power cord
- Barn doors
- Gel Frame
- Warranty card
- Quick Reference Guide