



## EVE P-130 RGB

EVE P-130 RGB is a robust RGB wash light designed for mobile lighting entertainers. Interchangeable magnetic lenses are included to alter the beam to desired angles. EVE P-130 RGB has a sturdy cast aluminum housing that provides extra strength without added weight. [D-Fi USB](#) compatibility is also onboard providing the option for wireless master/slave or DMX control. Its fanless design ensures 100% silent operation and the unit's high-frequency LED dimming offers flicker-free operation perfect for video use. EVE P-130 RGB has a built-in gel frame holder and 6¼-inch accessory slot to hold barn doors. Flexible control connection options are onboard with both 3- and 5-pin DMX connectors. PowerCON®-compatible power input/output connections allow secure power linking.



# Highlights

- Robust wash light designed for mobile lighting professionals
- Included interchangeable magnetic lenses alter the beam to desired angles
- Built-in gel frame holder and 6¼-inch accessory slot to hold barn doors
- powerCON®-compatible power input/output connections for power linking
- Fanless design ensures 100% silent operation
- Flexible control options with onboard 3- and 5-pin DMX connectors
- Flicker-free on video due to the high-frequency LED dimming
- D-Fi USB compatibility for wireless master/slave or DMX control
- Cast aluminum housing provides extra strength without the weight
- Fits best in the [CHS-40](#) VIP gear bag



25° and 45° lenses included

## Specifications

- DMX Channels: 3 or 9
- DMX Connectors: 3- and 5-pin XLR
- Light Source: 40 LEDs (13 red, 13 green, 14 blue) 130 W total, (2.5 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 34 Hz
- PWM Frequency: 2 kHz
- Beam Angle: 25°, 35° or 45°
- Field Angle: 45°, 55° or 65°
- Illuminance: (25°): 2190 lux @ 2 m  
(35°): 1100 lux @ 2 m (no lens installed)  
(45°): 727 lux @ 2 m  
(25°): 622 lux @ 5 m  
(35°): 322 lux @ 5 m (no lens installed)  
(45°): 194 lux @ 5 m
- Power Linking: 8 units @ 120 V; 16 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 122 W, 1.2 A @ 120 V, 60 Hz  
111 W, 0.5 A @ 230 V, 50 Hz
- Weight: 7.6 lbs (3.5 kg)
- Size: 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)
- Approvals: CE, MET
- Optional Controllers: [D-Fi USB](#)
- Accessory Holder/Gel Frame Size: 6.25 in (159 mm)

## What's Included

- Eve P-130 RGB
- 25° and 45° lenses
- Gel frame
- Power cord