



Freedom Par Quad-4 IP

Freedom Par Quad-4 IP is a 100% TRUE wireless, battery-operated, quad-color (RGBA) LED Par with built-in D-Fi transceiver. Its temporary outdoor-rated robust housing repels water, snow, dirt, and sand for all-weather applications and is available in black or white. Freedom Par Quad-4 IP works in Master/Slave mode with first-generation Freedom Pars and it has multiple wireless triggering and control options via the [FlareCON Air](#) and the FlareCON app. Convenient, wireless non-DMX control is available using the IRC-6 remote and customized colors can be created using the built-in LED display. Shine light where it is needed using the built-in adjustable kickstand and prevent light spillage with the built-in glare shield. Achieve smooth LED fading with built-in dimming curves and extend the battery's lifespan with built-in discharge protection. Safely store and transport your fixtures from gig to gig in the [CHS-FR4](#) carry bag. White housing not available in European Markets.



Highlights

- Temporary outdoor-rated robust housing repels water, snow, dirt, and sand for all-weather applications
- 100% TRUE wireless, battery-operated, quad-color (RGBA) LED Par with built-in D-Fi transceiver
- Multiple wireless triggering and control options via the FlareCON Air and the FlareCON app
- Works in Master/Slave with first-generation Freedom Pars
- Shine light where it is needed using the built-in adjustable kickstand
- Built-in glare shield prevents light spillage
- Extend the battery's lifespan with built-in discharge protection
- Convenient, wireless non-DMX control using the IRC-6 remote
- Create customized colors using the built-in LED display
- Achieve smooth LED fading with built-in dimming curves
- Suitable for every event with either black or white housing
- Safely store and transport your fixtures from gig to gig in the CHS-FR4 carry bag
- Compact and lightweight design easily fits inside sticks of TRUSST



Built-in glare shield



Built-in adjustable kickstand and IP Rated Control Panel



Threaded hole for truss mounting option



Fits inside sticks of TRUSST



Carrying handle

Specifications

- DMX Channels: 4, 6 or 10
- Light Source: 4 LEDs (quad-color RGBA) 5 W, (2 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 25 Hz
- PWM Frequency: 1,200 Hz
- Beam Angle: 15°
- Field Angle: 29°
- Maximum Run Time: (all on): up to 8 hours(single color): 20 hours
- Recharge Time: 7 hours
- Operating Frequency: 2.412 to 2.484 GHz
- Illuminance: 2,464 lux @ 2 m
- IP Rating: IP54
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 43 W, 0.6 A @ 120 V, 60 Hz (73 VA) 40 W, 0.3 A @ 230 V, 50 Hz (76 VA)
- Weight: 8.0 lb (3.6 kg)
- Size: 5.7 x 5.4 x 7.5 in (145 x 138 x 191 mm)
- Approvals: CE, FCC

What's Included

- IRC-6
- Power Cord
- Quick Reference Guide
- Warranty Card
- Stickers