



Intimidator Beam 140SR

Intimidator Beam 140SR is a cutting-edge moving head beam fitted with a bright 140 W discharge light engine. Its motorized frost filter converts the tight beam to a wide wash for different applications and an impressive 16-facet prism splits the beam and intensifies the display. The built-in totem mode keeps the light on and over the dance floor. Non-DMX control is available with the optional [IRC-6 wireless remote](#). On-board power linking saves time running extension cords. A unique ¼-turn hanging bracket allows for single or dual clamp mounting options. Fits best in the [CHS-50 VIP gear bag](#)



Highlights

- Cutting-edge moving head beam fitted with an intense 140 W discharge light engine
- Impressive 16-facet prism splits the beam and intensifies the excitement
- Motorized frost filter converts the tight beam to a wide wash for different applications
- Built-in totem mode keeps the light on and over the dance floor
- Unique ¼-turn hanging bracket allows for single or dual clamp mounting options
- Non-DMX control with the optional [IRC-6](#) wireless remote
- On-board power linking saves time running extension cords
- Motorized Focus
- Fits best in the [CHS-50](#) VIP gear bag

Specifications

- DMX Channels: 8 or 14
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt
- Colors: 14 + white, split colors, continuous scroll at variable speeds
- Gobos: 17 + open (all aluminum), fixed, continuous scroll at variable speeds
- Light Source: (included): Osram Sirius HRI 140 W discharge lamp (6,000 hrs)
(optional): Osram Sirius HRI 132 W discharge lamp (6,000 hrs)
- Strobe Rate: 0 to 20 Hz
- Beam Angle: (beam): 3°
(frost): 21°
- Illuminance: (5 m): 381,500 lux
(15 m): 37,900 lux
- Power Linking: 3 units @ 120 V; 6 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 228 W, 2 A @ 120 V, 60 Hz
224 W, 1.2 A @ 230 V, 50 Hz
- Weight: 25.8 lb (11.7 kg)
- Size: 12.7 x 8.6 x 16.5 in (322 x 220 x 420 mm)
- Approvals: CE, MET
- Optional Controllers: IRC-6
- Prism: 16-facet round, bidirectional rotation at variable speeds

What's Included

- Power cord
- Hanging bracket
- Warranty card
- Quick Reference Guide