



# Intimidator Beam LED 350

The Intimidator Beam LED 350 projects a tight, 4-degree, super-bright beam. Complete with an 8-position color wheel, a 5-position fixed gobo wheel with an animation effect, and a 3-facet prism, this light cuts through haze with lightning-fast speed, creating a brilliant shaft of light and defined aerial effects. This fixture can also serve dual roles, by utilizing the frost filter you can attain effective wash effect as well.



# Highlights

- Feature-packed moving head beam fitted with a 75W LED
- Emits bright, long-throw effects with tight, concentrated beam angles
- Convert the beam to a wash light using the motorized frost filter
- Easily generate complex looks using the fixed gobo wheel plus animation effect
- Split the beam and cover larger areas with the crisp 3-facet prism
- Create spectacular aerial light shows using extremely fast pan and tilt speeds
- Project light where you want it with user-selectable pan and tilt ranges
- Increase effects with electronic dimming and strobe features
- Create large, coordinated light shows with Intimidator™ Spot LED 350 in master/slave mode
- Continuous shows with individual reset of pan/tilt, color, gobo and prism
- Minimize programming time with built-in movement macros and move-in-black features
- Save time running cables and extension cords by power linking multiple units (US/UK only)
- Built-in, sound-activated programs dance to the beat of the music

## Specifications

- DMX Channels: 8 or 14
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540° / 270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 5 + open, animation effect, continuous scroll at variable speeds
- Light Source: 1 LED (white) 75 W (17 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 4°
- Illuminance: 139,200 lux @ 2 m
- Power Linking: 3 units @ 120 V, 7 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 258 W, 2.1 A @ 120 V, 60 Hz 269 W, 1.2 A @ 230 V, 50 Hz
- Weight: 22 lb (9.8 kg)
- Dimensions: 11.3 x 13.4 x 18.5 in (287 x 340 x 470 mm)
- Approvals: CE

## What's Included

- Power Cord
- Hanging bracket with mounting hardware
- Warranty Card
- Quick Reference Guide