



Intimidator Scan LED 200

It's a bright, compact LED scanner with tons of features, like built-in movement macros and move-in-black features, silent electronic dimming and strobe features, awesome sound-activated programs and easy access to built-in automated programs to generate a synchronized show in master/slave mode. Its high-frequency LED dimming allows for flicker-free video operation, plus you can power link up to 8 units to save time running cables and extension cords.



Highlights

- Bright and compact LED scanner packed with features to enhance any show
- Increase design flexibility and effects with 7 gobos plus 7 separate, saturated colors
- Minimize programming time using built-in movement macros and move-in-black features
- Increase effects with electronic dimming and strobe features
- Continuous shows with individual reset of pan/tilt, color and gobos
- Achieve flicker-free video operation with high-frequency LED dimming
- Save time running cables and extension cords by power linking multiple units (US version only)
- Increase mounting options with the included double-bracket yoke that doubles as a floor stand
- Sound-activated programs dance to the beat of the music
- Generate a synchronized show in master/slave mode with easy-to-access, built-in automated programs

Specifications

- DMX Channels: 5 or 8
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 180°/90°
- Colors: 7 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open, continuous scroll at variable speeds
- Light Source: 1 LED (white) 15 W (1 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 15°
- Illuminance: 1,577 lux @ 2 m
- Power Linking: 11 units @ 120 V; 21 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 80 W, 0.7 A @ 120 V, 60 Hz
86 W, 0.4 A @ 230 V, 50 Hz
- Weight: 7.5 lb (3.4 kg)
- Dimensions: 13.2 x 6.6 x 14.5 in (335 x 168 x 368 mm)
- Approvals: CE, MET

What's Included