



# Intimidator Scan LED 300

It's a bright, compact LED scanner with a crisp, 3-sided prism which duplicates the beam for great effects and a larger coverage area. Its high-frequency LED dimming allows for flicker-free video operation and it's packed with tons of features to enhance any show. It features a motorized focus for crisp gobos, sound-activated programs, and built-in automated programs for a synchronized show in master/slave mode. Plus, you can power link up to 4 units and save some time running cables and extension cords.



# Highlights

- Bright, and compact LED scanner packed with features to enhance any show
- Increase design flexibility and effects with interchangeable, rotating gobos plus separate, saturated colors
- Minimize programming time with built-in movement macros and move-in-black features
- Project crisp gobo from nearly any distance with the motorized focus
- Increase effects with electronic dimming and strobe features
- Split the beam and cover larger areas with the crisp, 3-facet prism
- Continuous shows with individual reset of pan/tilt, color, gobo, prism
- Achieve flicker-free video operation with high-frequency LED dimming
- Save time running cables and extension cords by power linking multiple units (US version only)
- Sound-activated programs dance to the beat of the music
- Generate a synchronized show in master/slave mode with easy-to-access, built-in automated programs

## Specifications

- DMX Channels: 8 or 11
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 180°/90°
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open (5 metal + 2 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable speeds
- Light Source: 1 LED (white) 60 W (14.9 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 21°
- Illuminance: 2,850 lux @ 2 m
- Power Linking: 3 units @ 120 V; 7 units @ 230 V
- Input Voltage: 120/230 VAC, 50/60 Hz (switchable)
- Power and Current: 236 W, 2 A @ 120 V, 60 Hz 237 W, 1 A @ 230 V, 50 Hz
- Gobo Size: 23.8 mm outside, 20.9 mm image, 2 mm max thickness
- Weight: 14.7 lb (6.7 kg)
- Dimensions: 11 x 10 x 18.9 in (279 x 254 x 478 mm)
- Approvals: CE, MET

## What's Included