



Intimidator Spot 260

Give your mobile performances some lighting punch with the feature-packed Intimidator Spot 260. It features a 75W LED and motorized focus that lets you project crisp gobos from nearly any distance. Throw light farther by decreasing the beam angle 5° using the manual zoom. Keep the party energized using Totem mode that keeps beams on the dance floor and a 3-facet prism splits the beam and covers a larger area to thrill event guests. Intimidator Spot 260 lets you set, save, and recall 1 scene manually, directly from the full-color LCD display. Link up to 4 fixtures to create eye-catching, synchronized shows in Automated or Sound mode. You can also use convenient, wireless non-DMX control using the optional IRC-6 remote. Intimidator Spot 260 has powerCON®-compatible power input/output connections for power linking. Fits best in the CHS-2xx VIP Gear Bag.



Highlights

- Feature-packed moving head fitted with a 75W LED designed for mobile performances
- ¼-turn hanging bracket allows for quick removal when needed
- Project crisp gobos from nearly any distance with the motorized focus
- Throw light farther by decreasing the beam angle 5° using the manual zoom
- 3-facet prism splits the beam and covers a larger area
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Link up to 4 fixtures to create eye-catching, synchronized shows in Automated or Sound mode
- Convenient, wireless non-DMX control using the optional [IRC-6](#) remote
- powerCON®-compatible power input/output connections for power linking
- Fits best in the [CHS-2xx](#) VIP Gear Bag

Specifications

- DMX Channels: 8 or 14
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/234°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/234°, 180°, 90° tilt
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open (6 metal + 1 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable speeds
- Light Source: 1 LED (white) 75 W, (3.3 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20.6 Hz
- Illuminance: (12°): 12,030 lux @ 2 m
(17°): 8,950 lux @ 2 m
- Power Linking: 5 units @ 120 V; 10 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 107 W, 1.5 A @ 120 V, 60 Hz
103 W, 0.8 A @ 230 V, 50 Hz
- Gobo Size: 24 mm outside, 20 mm image, 1.1 mm max thickness
- Zoom Angle: (manual): 12° to 17°
- Weight: 12.2 lb (5.6 kg)
- Size: 9.1 x 6.4 x 13.8 in (232 x 163 x 351 mm)
- Approvals: CE
- Prism: 3-facet round, static
- Optional Controllers: [IRC-6](#)

What's Included

- Intimidator Spot 260 IRC
- Power cord
- Hanging bracket with mounting hardware