



Intimidator Spot 355Z IRC X2

This moving head combo pack includes 2 Intimidator Spot 355Z IRC fixtures in one road case. The case's tall lid allows the included hanging brackets to remain on the fixtures during transportation, saving time on installation and take-down. The case has an additional central storage compartment perfect for storing cables, clamps, brackets or other accessories. Multiple cases can be stacked saving floor space and dual handles on each side make maneuvering easy. Locking casters prevent accidental rolling and the elastically hinged lid ensures the strap never gets caught when closing the lid.



Highlights

- Exceptionally bright, 90 W LED moving head spot designed for large events
- Motorized zoom for short-throw or long-throw applications
- Simple navigation and full text readout with the high-contrast, full-color LCD display
- Includes a FREE wedding-ready gobo pack that can be installed quickly and easily
- Works with the IRC-6 for wireless control and triggering
- Power link multiple units to save time running extension cords
- Easy-access gobo door allows for quick gobo changes without opening the fixture
- Emit crisp projections at almost any distance using the motorized focus
- 3-facet rotating prism splits the beam for great effects and to cover a larger area
- Built-in effect macros and move-in-black feature minimizes programming time
- Activate built-in, automated and sound-activated programs, or control in DMX or Master/Slave mode
- Project light where you want it with user-selectable pan and tilt ranges
- Fits best in the CHS-50 VIP Gear Bag

Specifications

- DMX Channels: 9 or 15
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open (5 metal + 2 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source: 1 LED (white) 90 W (3.2 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 23 Hz
- PWM Frequency: 2 kHz
- Illuminance: (10°): 35,225 lux @ 2 m (17°): 11,800 lux @ 2 m
- Power Linking: 4 units @ 120 V; 7 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 309 W, 3.2 A @ 120 V, 60 Hz 283 W, 1.6 A @ 230 V, 50 Hz
- Gobo Size: 24 mm outside, 20 mm image, 1.1 mm max thickness
- Zoom Angle: (motorized): 10° to 17°
- Weight: 27.4 lb (12.4 kg)
- Size: 13.4 x 9.7 x 18 in (340 x 248 x 456 mm)
- Approvals: CE
- Optional Controllers: IRC-6
- Prism: 3-facet round, static, bidirectional rotation at variable speeds

What's Included