



Intimidator Spot LED 350

Intimidator Spot LED 350 is one of the most powerful fixtures in the acclaimed [Intimidator](#) line. A 75-watt LED and superior optics make this fixture considerably brighter than most higher watt LED fixtures currently on the market. This feature-packed moving head includes a motorized focus for projecting crisp, rotating gobos from most distances. A rotating 3-facet prism splits the beam for maximum effects and coverage, while interchangeable gobos let you vary and customize the show.



Highlights

- Feature-packed, moving head spot fitted with a 75 W LED
- Project crisp gobos from nearly any distance with the motorized focus
- Split the beam and cover a larger area using the 3-facet rotating prism
- Suitable for every event with either black or white housings
- Quickly and easily change gobos using the easy-access gobo door
- Achieve super-smooth LED fading with the built-in, electronic dimmer
- Throw light farther by decreasing the beam angle by 5° using the manual zoom
- Project light where you want it with user-selectable pan and tilt ranges
- Minimize programming time with built-in effect macros and move-in-black feature
- Save time running cables and extension cords by power linking multiple units
- Continuous shows with individual reset of pan/tilt, color, gobo, prism and focus
- Sound-activated programs dance to the beat of the music
- Generate a synchronized show in Master/Slave mode with easy-to-access, built-in automated programs
- Fits best in the CHS-50 VIP Gear Bag

Specifications

- DMX Channels: 8 or 14
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open, rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source: 1 LED (white) 75 W (17 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Illuminance: (12°): 9,490 lux @ 2 m (17°): 4,670 lux @ 2 m
- Power Linking: 3 units @ 120 V; 7 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 272 W, 2.2 A @ 120 V, 60 Hz 285 W, 1.2 A @ 230 V, 50 Hz
- Gobo Size: 24 mm outside, 20 mm image, 1.1 mm max thickness
- Zoom Angle: (manual): 12° to 17°
- Weight: 22.7 lb (10.3 kg)
- Size: 10.6 x 13.4 x 15.4 in (268 x 340 x 392 mm)
- Approvals: CE

What's Included

- Power cord
- Hanging bracket with mounting hardware
- Warranty card
- Quick Reference Guide