



## SlimPAR H6 USB

SlimPAR H6 USB is a low-profile RGBAW+UV LED washlight with D-Fi USB compatibility for wireless master/slave or DMX control. It also works in sound-active mode.

Built-in dimming curves provide smooth LED fading, and the 6-in-1 LED technology generates a broad spectrum of natural looking colors. Precise colors can also be created with the built-in LED display. Point-and-shoot operation of static colors and automated programs is possible with the optional [IRC-6](#) remote. Compact designed, it works as truss warmer. Easily transports in the optional [CHS-30 VIP Gear Bag](#).



# Highlights

- Low-profile LED PAR with 6-in-1 LED technology (RGBAW+UV)
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with 6-in-1 LED technology
- Point-and-shoot operation of static colors and automated programs with the optional IRC-6 remote
- Save time running cables and extension cords by power linking multiple units
- Multiple control options include DMX, Master/Slave and Sound-Active modes
- Create customized colors using the built-in LED display
- Achieve smooth LED fading with built-in dimming curves
- Flicker-free operation suitable for on-camera use
- Easily transports in the optional CHS-30 VIP Gear Bag
- Sleek and lightweight to easily fit inside sticks of TRUSST®

## Specifications

- DMX Channels: 6, 8 or 12
- DMX Connectors: 3-pin XLR
- Light Source: 6 LEDs (hex-color RGBAW+UV) 10 W (2.4 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 18 Hz
- PWM Frequency: 1.2 kHz
- Beam Angle: 23°
- Field Angle: 41°
- Illuminance: 747 lux @ 2 m
- Power Linking: 20 units @ 120 V; 39 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 25 W, 0.4 A @ 120 V, 60 Hz 23 W, 0.2 A @ 230 V, 50 Hz
- Weight: 3.4 lb (1.6 kg)
- Size: 8.3 x 3.6 x 9.6 in (211 x 91.5 x 244 mm)
- Approvals: CE
- Optional Controllers: IRC-6, D-Fi USB

## What's Included

- Power cord
- Warranty card
- Quick Reference Guide
- User Manual