



## SlimPAR Pro Tri

It utilizes the latest in tri-color LEDs delivering a uniform output. Eighteen tri-color (RGB) LEDs power the fixture and the color is mixed before the lens which limits any undesirable effects of multi-colored shadows.

Eliminating multi-colored shadows also allows the unit to serve admirably as front light.



# Highlights

- LED Par designed for any application in need of a low-profile, tri-color LED wash light
- Nearly eliminate multicolored shadows with high-power, tri-color LEDs
- Emits a smooth, even output perfect for front light applications
- Ideal for quiet applications due to silent operation and no moving parts
- Flicker-free operation suitable for use on-camera use
- Achieve super-smooth LED fading with built-in dimming curves that simulate existing lighting
- Ensure a secure power cord with the locking IEC power input (US only)
- Trigger eye-catching effects with built-in, automated programs via master/slave or DMX mode
- Increase stand-alone versatility with multiple user-configurable settings
- Save time running cables and extension cords by power linking multiple units
- Fits best in the CHS-30 VIP Gear Bag

## Specifications

- DMX Channels: 3, 4, or 9
- DMX Connectors: 3-pin XLR
- Light Source: 18 LEDs (tri-color RGB) 3 W (1,050 mA), 50,000 hours life expectancy
- PWM Frequency: 1,200 Hz
- Beam Angle: 21°
- Field Angle: 42°
- Illuminance: 1,980 lux @ 2 m
- Power Linking: 9 units @ 120 V; 16 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 97 W, 0.8 A @ 120 V, 60 Hz 102 W, 0.5 A @ 230 V, 50 Hz
- Weight: 6.4 lb (2.9 kg)
- Size: 3.7 x 10.1 x 11.4 in (94 x 256 x 290 mm)
- Approvals: CE, MET

## What's Included

- External power cord
- Gel frame holder
- Hanging bracket with mounting hardware
- Quick Reference Guide
- Warranty card