

4Bar Flex Q ILS

HIGHLIGHTS

- Complete wash lighting solution fitted with high-intensity, quad-color (RGBA) LEDs
- ILS compatibility for use in the ILS ecosystem
- Mounts to most tripods or speaker stands, without the need for additional clamps, using the pass-through hole
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with punchy amber LEDs
- D-Fi™ USB compatibility for wireless master/slave or DMX control
- Create the ultimate light show by mounting up to 4 additional fixtures to the top of the 4Bar Flex Q
- Provide electricity to the additional lights by using the built-in Edison plugs
- Maximize setup possibilities and configurations with 2 included L-brackets
- Easily set up and tear down in minutes with the included carrying bag
- Multiple control options include standalone, DMX mode, wireless footswitch or the IRC-6 remote
- Safely mounts to truss using built-in bolts



SPECIFICATIONS

- DMX Channels : 4, 6 or 19
- DMX Connectors : 3-pin XLR
- Max Unobstructed Distance : 28 LEDs (quad-color RGBA) 3.5 W, (1.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 14°
- Field Angle : 23°
- Illuminance : 2,353 lux @ 2 m (per pod)
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
80 W, 1.2 A @ 120 V, 60 Hz
78 W, 0.6 A @ 230 V, 50 Hz
- Approvals : CE, RoHS, UKCA
- Operating Frequency (D-Fi) : 2.412 to 2.484 GHz
- Operating Frequency (foot switch) : 433 MHz
- Max Unobstructed Distance (foot switch) : 100 ft (30.5 m)
- Footswitch battery : 9 V
- Fits Tripod Sizes : 1.5 in (36.80 mm)
- Bracket Mounting Hole : M10 (1.5 mm pitch)
- Weight : 12.2 lb (5.5 kg)
- Weight (Controller) : 1.2 lb (0.6 kg)
- Size : 45.7 x 2 x 12 in (1186 x 50.8 x 305 mm)
- Size (Controller) : 16.5 x 5.2 x 1.5 in (419 x 132 x 38 mm)
- Included controller : IRC-6
- Optional controller : D-Fi USB

WHAT'S INCLUDED

- 4Bar Flex Q ILS
- Power cord
- Carrying bag
- Wireless footswitch
- IRC-6 remote
- Quick Reference Guide