

4BAR Flex T USB

HIGHLIGHTS

- Upgraded version of the popular 4BAR Tri USB increases FLEXibility
- Mounts to most tripods or speaker stands, without the need for additional clamps, using the pass-through hole
- D-Fi™ USB compatibility for wireless master/slave or DMX control
- Create the ultimate light show by mounting up to 4 additional fixtures to the top of the 4BAR Flex
- Provide electricity to the additional lights by using the built-in Edison plugs
- Maximize setup possibilities and configurations with 2 included L-brackets
- Easily set up and tear down in minutes with the included carrying bag
- Multiple control options include standalone, DMX mode, wireless footswitch or the IRC-6
- Safely mounts to truss using built-in bolts
- Create large, coordinated light shows with other 4BAR fixtures in master/slave mode



SPECIFICATIONS

- DMX Channels : 3 or 15
- DMX Connectors : 3-pin XLR
- Light Source : 28 LEDs (tri-color RGB) 3 W, (800 mA), 50,000 hours life expectancy
- Strobe Rate : 0 to 22 Hz
- Beam Angle : 18° (per pod)
- Field Angle : 31° (per pod)
- Fits Tripod Size : 1.2 – 1.5 in (32 – 39mm)
- Illuminance : 2330 lux @ 2 m (per pod)
- Power Linking : 8 units @ 120 V; 16 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 64 W, 1 A @ 120 V, 60 Hz
63 W, 0.5 A @ 230 V, 50 Hz
- Weight : 11.6 lb (5.3 kg)
(Controller): 0.8 lb (1.8 kg)
- Size : 47.4 x 5.5 x 14.75 in (1205 x 140 x 374.8 mm)
(Controller): 12.4 x 5.2 x 1.5 in (315 x 131.5 x 37.5 mm)
- Approvals : CE
- Optional Controllers : IRC – 6, D-Fi USB

WHAT'S INCLUDED

- 4Bar Flex T USB
- Power cord
- Carrying bag
- Wireless Footswitch
- Warranty card
- Quick Reference Guide