4BAR ILS

HIGHLIGHTS

- Complete wash lighting solution designed for mobile entertainers
- ILS compatibility for use in the ILS ecosystem
- Achieve total room or stage coverage with 4 individually adjustable heads
- D-Fi USB compatibility for wireless master/slave or DMX control
- Easily set-up and tear down in minutes using the included tripod, wireless footswitch and carry bags
- Increase mounting options by safely mounting to truss using the built-in bolts
- Create large, coordinated light shows with other 4BAR fixtures in master/slave mode
- Sound-activated programs dance to the beat of the music
- Easily control static colors and automated programs with the optional IRC-6 remote
- Generate a synchronized show in master/slave mode with easy-toaccess, built-in automated programs

SPECIFICATIONS

- DMX Channels : 3, 5 or 15
- DMX Connectors : 3-pin XLR
- Light Source : 432 LEDs (144 red, 144 green, 144 blue) 0.25 W, (20 mA), 100,000 hours life expectancy.
- Strobe Rate : 0 to 19.9 Hz
- Beam Angle : 17°
- Field Angle : 24°
- Illuminance : 786 lux @ 2 m (per pod)
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 29 W, 0.4 A @ 120 V, 60 Hz 27 W, 0.2 A @ 230 V, 50 Hz
- Weight : 11 lb (5.0 kg)
- Size : 43.3 x 2 x 10.5 in (1,100 x 50 x 267 mm)
- Approvals : CE, RoHS, UKCA
- Stand Height : 7 ft 4 in (2.2 m)
- Fits Tripod Sizes : 1.37 in (35 mm)
- Weight (Controller) : 1.2 lb (0.6 kg)
- Size (Controller) : 12.4 x 5.2 x 1.5 in (315 x 132 x 38 mm)
- Optional Controllers : IRC-6, D-Fi USB

WHAT'S INCLUDED

- 4Bar ILS
- Power cord
- Carrying bag
- Tripod
- Tripod Carry bag
- Wireless Footswitch
- Quick Reference Guide

