4BAR LTBT ILS

HIGHLIGHTS

- Complete wash lighting solution with built-in Bluetooth® wireless technology
- Control directly from a smart phone or tablet without any additional hardware
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless master/slave or DMX
- Easily set up and tear down in seconds with the included tripod, carry bags and footswitch
- Create large, coordinated light shows with other 4BAR fixtures in master/slave mode.
- Out of the box wireless control with included footswitch or optional IRC-6 controller
- Achieve total room or stage coverage with 4 individually adjustable heads.
- Easily control static colors and automated programs with the optional IRC-6 remote
- Sound-activated programs dance to the beat of the music.



- DMX Channels: 3, 5 or 15 DMX Connectors: 3-pin XLR Max Unobstructed Distance: 150 ft (45.7 m) Light Source: 12 LEDs (tri-color RGB) 3 W, 1 A, 50,000
- hours life expectancy Strobe Rate : 0 to 22 Hz

- Beam Angle : 12° Field Angle : 21° Fits Tripod Size : 1 in (25.4 mm)
- Illuminance : 2,382 lux @ 2 m (per pod)
 Power and Current :

- 47 W, 0.7 A @ 120 V, 60 Hz 45 W, 0.4 A @ 230 V, 50 Hz Weight: 7.8 lb (3.5 kg) Size: 36.1 x 3.7 x 10.8 in (918 x 95 x 274 mm) Approvals: CE, ROHS, UKCA, FCC Stand Height: 50-83 in (127-211 cm)
- Optional Controllers : IRC-6, BTAir, ILS Bluetooth Version : 4.2
- Operating Frequency: 2.4 GHz

WHAT'S INCLUDED

- **4BAR LTBT ILS**
- Power cord
- Carrying bag
- Hanging Bracket
- Tripod
- Footswitch
- Quick Reference Guide



