

# 4BAR Quad

## HIGHLIGHTS

- Complete wash lighting solution fitted with high-intensity, quad-color (RGBA) LEDs
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with punchy amber LEDs
- Out of the box wireless control with included footswitch or optional IRC-6 controller
- Easily set up and tear down in minutes with the included tripod stand and carrying bags
- D-Fi™ USB compatibility for wireless Master/Slave or DMX control
- Achieve total room or stage coverage with 4 individually adjustable heads
- Increase mounting options by safely mounting to truss using built-in bolts



## SPECIFICATIONS

- DMX Channels : 4, 6 or 19
- DMX Connectors : 3-pin XLR
- Max Unobstructed Distance : (foot switch): 100 ft (30.5 m)
- Light Source : 28 LEDs (quad-color RGBA) 3.5 W, (1.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- PWM Frequency : 1310 Hz
- Beam Angle : 14°
- Field Angle : 23°
- Operating Frequency : (D-Fi): 2.412 to 2.484 GHz  
(foot switch): 433 MHz
- Fits Tripod Size : 1.5 in (36.80 mm)
- Illuminance : 2,353 lux @ 2 m (per pod)
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 80 W, 1.2 A @ 120 V, 60 Hz  
78 W, 0.6 A @ 230 V, 50 Hz
- Weight : 12.2 lb (5.5 kg)  
(Controller): 1.2 lb (0.6 kg)
- Size : 45.7 x 2 x 12 in (1186 x 50.8 x 305 mm)  
(Controller): 16.5 x 5.2 x 1.5 in (419 x 132 x 38 mm)
- Approvals : CE, FCC
- Footswitch battery : 9 V
- Stand Height : 7 ft 4 in (2.2 m)
- Bracket Mounting Hole : M10 (1.5 mm pitch)
- Optional Controllers : IRC-6, D-Fi USB

## WHAT'S INCLUDED

- 4Bar Quad
- Power cord
- Carrying bag
- Tripod
- Tripod Carry bag
- Wireless Footswitch
- Quick Reference Guide