

4BAR Tri USB

HIGHLIGHTS

- Complete wash lighting solution fitted with high-intensity, tri-color (RGB) LEDs
- Out of the box wireless control with included footswitch or optional IRC-6 controller
- Easily set up and tear down in minutes with the included tripod stand and carrying bags
- Create large, coordinated light shows with other 4BAR™ fixtures in Master/Slave mode
- D-Fi™ USB compatibility for wireless Master/Slave or DMX control
- Create the ultimate light show by mounting up to 4 additional fixtures to the top of the 4BAR™ Tri USB
- Achieve total room or stage coverage with 4 individually adjustable heads
- Nearly eliminate multi-colored shadows with high-power, tri-color (RGB) LEDs
- Increase mounting options by safely mounting to truss using built-in bolts
- Save time running cables and extension cords by power linking multiple units
- Sound-activated programs dance to the beat of the music



SPECIFICATIONS

- DMX Channels : 3 or 15
- DMX Connectors : 3-pin XLR
- Light Source : 28 LEDs (tri-color RGB) 3 W (1 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 25 Hz
- PWM Frequency : 1,200 Hz
- Beam Angle : 18°
- Field Angle : 31°
- Fits Tripod Size : 1.34 to 1.57 in (35 to 40 mm)
- Illuminance : 2,330 lux @ 2 m (per pod)
- Power Linking : 8 units @ 120 V; 14 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 69 W, 1 A @ 120 V, 60 Hz
66 W, 0.5 A @ 230 V, 50 Hz
- Weight : 20.6 lb (10.8 kg)
(Controller): 0.8 lb (1.8 kg)
- Size : 41.3 x 2 x 10.6 in (1,050 x 50 x 270 mm)
(Controller): 12.4 x 5.2 x 1.5 in (315 x 132 x 38 mm)
- Approvals : CE
- Optional Controllers : IRC-6, D-Fi™ USB
- Stand Height : 7.4 ft (2.25 m)

WHAT'S INCLUDED

- Power cord
- 4BAR and Stand carry bag
- Tripod
- Wireless Footswitch
- Quick Reference Guide / Warranty card