COREpar 40 USB

HIGHLIGHTS

- COB (Chip-on-Board) LED produces a full spectrum of light with unsurpassed color mixing
- D-Fi™ USB compatibility for wireless Master/Slave or DMX control
- Included magnetic Fresnel lens allows the flexibility to go from ultra-wide to narrow beam in seconds
- Withstand the harshness of traveling from gig to gig with a robust housing
- Sit-flat housing design hugs the floor and features power and DMX outlets on the side of the unit
- Achieve flicker-free video operation with high-frequency LED dimming
- Save time running cables and extension cords by power linking multiple units
- Point-and-shoot operation of static colors and automated programs with the optional IRC-6 remote
- Multiple control options include DMX, Master/Slave and Sound-Active modes
- Create customized colors using the built-in LED display
- Achieve smooth LED fading with built-in dimming curves
- Easily transports in the optional CHS-30 VIP Gear Bag
- Compact design easily fits inside sticks of TRUSST®



SPECIFICATIONS

DMX Channels: 3 or 8DMX Connectors: 3-pin XLR

Light Source: 1 COB LED (tri-color RGB) 40 W (2 A), 50,000 hours life expectancy

Strobe Rate: 0 to 33 Hz
PWM Frequency: 2,000 Hz
Beam Angle: 40° (without lens)

20° (with lens)

• Field Angle: 85° (without lens)

28° (with lens)

• Illuminance : 243 lux @ 2 m (without lens) 1,660 lux @ 2 m (with lens)

Power Linking: 11 units @ 120 V; 21 units @ 230 V

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

 Power and Current: 47 W, 0.7 A @ 120 V, 60 Hz 46W, 0.4 A @ 230 V, 50 Hz

• Weight: 3.4 lb (1.6 kg)

Size: 5.2 x 7.4 x 9.5 in (132 x 189 x 242 mm)

Approvals : CE

Optional Controllers : IRC-6

WHAT'S INCLUDED

Power cord

Magnetic Fresnel lens

Warranty card

Quick Reference Guide

Hanging bracket with mounting

