

Cumulus

HIGHLIGHTS

- Professional low-lying fog machine creates thick clouds that hug the floor
- Continuous operation produces fog on demand
- Ultrasonic agitator converts distilled water into a thin mist
- Fast heat up time allows for quick operation
- Rugged flight case makes transportation a breeze
- Control via an board digital display or DMX
- Locking casters prevent an accidental rollaway

SPECIFICATIONS

- DMX Channels : 2
- DMX Connectors : 3- and 5-pin XLR
- Heat-Up Time : 3 min
- Input Voltage : 120 VAC, 60 Hz or 230 VAC, 50 Hz
- Power and Current : 970 W, 8 A @ 120 V, 60 Hz
970 W, 4 A @ 230 V, 50 Hz
- Weight : 58.8 lb (26.7 kg)
- Size : 25 x 16 x 18 in (625 x 409 x 453 mm)
- Approvals : CE
- Tank Capacity : Fog Fluid Tank Capacity: .9 gal (3.25 l)
Water Tank Capacity: 2 gal (7.6 l)
- Output : 10,000 cfm
- Fog Fluid Consumption : 12 ml/min
- Water Consumption : 120 ml/min
- Compatible Fluids : LLG, LLF5

WHAT'S INCLUDED

- Cumulus

