

D-Fi Stream 6

HIGHLIGHTS

- Wireless DMX splitter provides 6 optically isolated outputs
- Operates on the popular D-Fi wireless DMX protocol for seamless transitioning into any rig
- Built-in D-Fi transceiver sends or receives DMX with the flick of a switch
- Wirelessly synchronize an unlimited number of D-Fi ready fixtures and receivers simultaneously
- Flexible inputs include a wired 3-pin DMX for non-wireless operation
- Versatile mounting options include M10 threaded holes for direct applications on TRUSST
- An additional pass-through connects to additional D-Fi Stream 6s without using an optically isolated port
- Electrical isolation between input and output keeps connected fixtures protected
- Conveniently mount in a single rack space (1U)
- Fully FCC/RTTE compliant



SPECIFICATIONS

- DMX Channels : 3-pin XLR
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 4 W, 0.04 A @ 120 V, 60 Hz
9 W, 0.05 A @ 230 V, 50 Hz
- Weight : 5.8 lb (2.6 kg)
- Size : 19 x 5.3 x 1.8 in (483 x 134 x 46 mm)
- Approvals : CE, FCC

WHAT'S INCLUDED

- Warranty card
- Quick Reference Guide