

EVE E-100Z

HIGHLIGHTS

- LED Ellipsoidal shines a hard-edged, warm white spot in any direction
- Easily highlight areas by altering the projected beam with framing shutters
- Flexibility to project from any distance using the manual zoom
- Flicker-free operation suitable for on-camera use
- Includes holders for glass and steel gobos and a gel frame
- Save time running extension cords by power linking multiple units
- Eliminate the need for DMX control with standalone operation



SPECIFICATIONS

- DMX Channels : 1 or 3
- DMX Connectors : 3-pin XLR
- Light Source : 1 LED (warm white) 100 W (2.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 30 Hz
- Illuminance : (14°): 15,100 lux @ 2 m
(30°): 3,800 lux @ 2 m
(14°): 3,238 lux @ 5 m
(30°): 829 lux @ 5 m
- Power Linking : 9 units @ 120 V; 16 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 106 W, 0.9 A @ 120 V, 60 Hz
103 W, 0.5 A @ 230 V, 50 Hz
- Gobo Size : M (66 mm outside, 48 mm image, 2 mm max thickness)
- Zoom Angle : (manual): 14° to 30°
- Weight : 12.6 lb (5.7 kg)
- Size : 24 x 7.2 x 16.9 in (611 x 183 x 430 mm)
- Approvals : CE, MET
- CRI : 80
- Color Temperature : 3,500 K
- Accessory Holder/Gel Frame Size : 6.3 x 6.3 in (160 x 160 mm)/6.24 x 6.24 in (158.5 x 158.5 mm)

WHAT'S INCLUDED

- Power cord
- Gel Frame
- Framing Shutters
- Gobo Holders for Glass and Steel Gobos
- Warranty card