

EVE P-140 VW

HIGHLIGHTS

- Robust, variable-white wash light designed for mobile lighting professionals
- Included interchangeable magnetic lenses alter the beam to desired angles
- Built-in gel frame holder and 6¼-inch accessory slot to hold barn doors
- powerCON®-compatible power input/output connections for power linking
- Fanless design ensures 100% silent operation
- Flexible control options with onboard 3- and 5-pin DMX connectors
- Flicker-free on video due to the high-frequency LED dimming
- D-Fi USB compatibility for wireless master/slave or DMX control
- Cast aluminum housing provides extra strength without the weight
- Fits best in the [CHS-40](#) VIP gear bag



SPECIFICATIONS

- DMX Channels : 3 or 9
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 40 LEDs (13 cool white, 13 warm white, 14 amber) 140 W total, (2.4 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 34 Hz
- PWM Frequency : 2 kHz
- Beam Angle : 35°, 41° or 56°
- Field Angle : 63°, 94° or 82°
- Illuminance : (35°): 2,793 lux @ 2 m (lens 1)
(41°): 2,082 lux @ 2 m (no lens installed)
(56°): 1,335 lux @ 2 m (lens 2)
(37°): 447 lux @ 5 m (lens 1)
(41°): 333 lux @ 5 m (no lens installed)
(56°): 214 lux @ 5 m (lens 2)
- Lumens : 5,443
- Power Linking : 8 units @ 120 V; 16 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 122 W, 1.2 A @ 120 V, 60 Hz
111 W, 0.5 A @ 230 V, 50 Hz
- Weight : 7.6 lbs. (3.5 kg)
- Size : 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)
- Approvals : CE, MET
- Color Temperature Range : 2700 to 13000 K
- Optional Controllers : [D-Fi USB](#)
- Accessory Holder/Gel Frame Size : 6.25 in (159 mm)
- CRI : 77

WHAT'S INCLUDED

- Eve P-140 VW
- Lens 1 and Lens 2
- Gel frame
- Power cord