Eve TF-20X

HIGHLIGHTS

- Soft edge accent luminaire designed for mobile and installation applications
- Constant Current Reduction (CCR) dimming works with conventional dimmers
- Track adaptor included fits most single and dual circuit tracks
- Suitable for every event with either black or white housing
- Classic Fresnel style gives the feeling of stage and theatrical
- Included barn doors block excess light from stage and unwanted areas
- Includes Gel frame to add custom colors when needed
- Achieve flicker-free video operation with CCR LED dimming
- Standard power cord attached for mobile use right out of the box
- Includes track light adaptor for easy addition to existing track lighting systems
- MET certified, perfect for retrofitting and new installations



SPECIFICATIONS

Light Source: 1 COB LED (warm white) 20 W, (0.5 A), 50,000 hours life expectancy

Beam Angle: 24° Field Angle: 40°

Illuminance: 1,506 lux @ 2 m

Lumens: 1,658

Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz

Power and Current: 24 W, 0.2 A @ 120 V, 60 Hz 24 W, 0.1 A @ 220 V, 50 Hz

Weight: 2 lbs (0.9 kg)

Size: 7.9 x 4.8 x 3.4 in (201.5 x 123 x 87.8 mm)

Approvals: CE, MET, UKCA, RoHS Color Temperature: : 2700 K

CRI: 91

Input Voltage: 220 VAC, 50 Hz Compatible Track: : Type H

WHAT'S INCLUDED

EVE TF-20X

Track adaptor

Barn doors

Gel frame

Quick Reference Guide



