

EZLink Strip Q6BT ILS

HIGHLIGHTS

SPECIFICATIONS

- DMX Channels : 4, 6 or 16
- DMX Connectors : 3-pin XLR
- Max Unobstructed Distance : 150 ft (45.7 m)
- Light Source : 4 LEDs (quad-color RGBA) 3 W, (1A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20Hz
- Beam Angle : 47°
- Field Angle : 79°
- Maximum Run Time :
 - All on: up to 8 hours
 - Single color: up to 20 hours
- Recharge Time : 4 hours
- Operating Frequency : 2.4 GHz
- Illuminance : 325 lux @ 2 m
- Power Linking : 33 units @ 120 V; 54 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 17 W, 0.3 A @ 120 V, 60 Hz
 - 17 W, 0.1 A @ 230 V, 50 Hz
- Weight : 6.8 lb (3.1 kg)
- Size : 19.7 x 4.2 x 5.4 in (500 x 108 x 139 mm)
- Approvals : CE, RoHS ,UKCA, FCC
- Cable Length : 5 ft (1.5 m)
- Bracket Mounting Hole : 13 mm
- Optional Controllers : IRC6, BTAir
- Bluetooth Version : 4.2



WHAT'S INCLUDED

- EZLink Strip Q6BT ILS
- Power cord
- Quick Reference Guide