

FLEXstand FX ILS

Simplify setups and get the party started faster with FLEXstand FX ILS, the multi-purpose stand that doubles as a lightshow. This heavy-duty timesaver has 68 built-in LEDs and auto programs that can be resized to fit the chosen stand height. Its trigger-style safety release enables DJs, performers, and event managers to make smooth and secure height adjustments on the fly. ILS, RF, and DMX control options mean this stand can be operated just like any other lighting fixture for flawlessly synced shows every time. Quickly achieve eye-catching mobile entertainment setups with FLEXstand FX ILS.

HIGHLIGHTS

- Multi-purpose, telescoping stand safely supports lighting and audio gear
- Built-in LED strip adds pizzazz and eye-candy effects to mobile entertainment setups
- Auto programs can be resized to fit the chosen height of the stand
- Built-in RF receiver and compatible with the RFC and RFC-XL remotes (sold separately)
- Compatible with the ILS ecosystem (DFI-USB sold separately)
- Different pole diameters accommodate clamps and taper into a speaker mount on top
- Trigger-style safety release allows the pole to descend safely
- Toolless design allows for fast and easy setup and tear down
- Threaded pole can be inserted into multiple positions for different applications
- Cast iron base includes rubber feet that won't scratch delicate floors and allows for quick retrieval



SPECIFICATIONS

- DMX Channels : 4, 15, 18, 34, 66, or 94
- DMX Connectors : 3-pin XLR
- Light Source : 68 LEDs (quad-color RGB+WW) 0.8W, 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Operating Frequency : 2.412 to 2.48 GHz
- Power Linking : 34 units @ 120 V; 47 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Approvals : CE, FCC
- Load Capacity : 132 lb (60 kg)
- Cable Length : 5 ft (1.52 m)
- Power and Current : 15 W, 0.2 A @ 230 V, 50 Hz
- Power and Current : 15 W, 0.3 A @ 120 V, 60 Hz
- Weight (pole) : 8.2 lbs (3.7 kg)
- Weight (base) : 34.2 lbs (16 kg)
- Weight (combined) : 42.4 lbs (19.2 kg)
- Threaded inserts (bottom) : M10-1.0 TPI
- Threaded insert (top) : M10-1.5 TPI
- Pole Height : 4.8 to 8 ft (1.5 to 2.4 m)
- Pole Diameter (Top) : 1.34 in (34 mm)
- 1.7 in (44 mm) : Pole Diameter (Bottom)
- 2 in (50 mm) : Optional Controllers

WHAT'S INCLUDED

- FLEXstand FX ILS
- Power cord
- Base
- Extension pole
- Carry Bag
- Cable clips (x2)
- QRG

