

Freedom Flex H4 IP X6

HIGHLIGHTS

- 100% TRUE wireless up light system complete with 6 Freedom Flex H4 IP pars, 6 Flex batteries and a charging road case
- Swappable battery packs ensures the fixture is always ready to go
- Charging road case simultaneously charges and holds 6 additional batteries (sold separately)
- Temporary outdoor-rated robust housing repels water, snow, dirt, and sand for all-weather applications
- Multiple wireless triggering and control options via the FlareCON Air and the FlareCON app
- Works in master/slave with all Freedom Pars
- Shine light where it is needed using the built-in adjustable kickstand
- Convenient, wireless non-DMX control using the IRC-6 remote
- Achieve smooth LED fading with built-in dimming curves
- Compact and lightweight design easily fits inside sticks of TRUSST



SPECIFICATIONS

- DMX Channels : 6, 8 or 12
- Max Unobstructed Distance : 600 ft (182.88 m)
- Light Source : 4 LEDs (hex-color RGBAW + UV) 10 W, (2 A), 50,000 hours life expectancy.
- Strobe Rate : 0 to 30 Hz
- PWM Frequency : 1.2 KHz
- Beam Angle : 23°
- Field Angle : 34°
- Recharge Time : 6 hours
- Illuminance : 2,163 lux @ 2 m
- Lumens : 1,138
- IP Rating : IP54
- Weight : 8.8 lb (4 kg)
- Size : 5.43 x 5.43 x 8.11 in (138 x 138 x 206 mm)
- Approvals : CE, FCC
- Maximum Run Time (all on) : up to 8 hours
- Maximum Run Time (single color) : up to 20 hours
- Startup Temperature : 32 °F to 122 °F (0 °C to 50 °C)
- Operating Temperature : -4 °F to 140 °F (-20 °C to 60 °C)
- Bracket Mounting Hole : M12
- Road Case Compatible Fixtures : Freedom Flex H4 IP
- Road Case Wheel Size : 3 in (76.2 mm)
- Road Case Weight : 96 lb (44 kg)
- Road Case Size : 21.9 x 20.1 x 10 in (555 x 510 x 255 mm)

WHAT'S INCLUDED

- x6 Freedom Flex H4 IP
- x6 Freedom Flex Batteries
- Power cord
- IRC-6 Remote
- Charging Road Case
- Quick Reference Guide