

Freedom Par H9 IP

HIGHLIGHTS

- 100% TRUE wireless, battery-operated, hex-color LED uplight with built-in D-Fi transceiver
- Robust housing repels mother nature for temporary outdoor situations
- New secondary optics provide perfect color blending with nearly no artifacts
- Magnetic diffuser pops on or off with ease and widens the coverage area
- Adjustable run times ensure the fixture will last the length of the event
- OLED display allows for full-text and to easily change fixture's settings
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- Adjust the projection angle using the spring-loaded kickstand
- Built-in glare shield protects light spillage and eye fatigue
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Achieve smooth LED fading with built-in dimming curves
- Compact and lightweight design easily fits inside sticks of TRUSST®



SPECIFICATIONS

- DMX Channels : 6, 8 or 16
- Max Unobstructed Distance : 600 ft (183 m)
- Light Source : 9 LEDs (hex-color RGBAW+UV, 10 W, (5.7A), 50,000 hours life expectancy)
- Strobe Rate : 1 to 25 Hz
- Beam Angle : 23°
- Field Angle : 46°
- Recharge Time : 3 hours
- Operating Frequency : 2.412 to 2.484 GHz
- Illuminance : 1249 lux @ 2 m
- Lumens : 1,258
- IP Rating : IP54
- Input Voltage : 24 VDC, 1.5 A (external power supply: 24 VDC, 50/60 Hz)
- Power and Current :
 - 50 W, 0.7 A @ 120 V, 60 Hz
 - 50 W, 0.4 A @ 230 V, 50 Hz
- Weight : 4.6 lbs (2.1 kg)
- Size : 4.7 x 4.7 x 4.9 in (120 x 120 x 126 mm)
- Approvals : CE, UKCA, RoHS, FCC
- Beam Angle (with diffuser) : 40°
- Field Angle (with diffuser) : 79°
- Illuminance (with diffuser) : 432 lux @ 2 m
- Run Time (adjustable) : 3, 5, 8, or 12 hrs
- Startup Temperature : 4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature : -22 °F to 113 °F (-30 °C to 45 °C)
- Bracket Mounting Hole : M12
- Optional Controllers : RFC, RFC-XL, FlareCON

WHAT'S INCLUDED

- Freedom Par H9 IP
- External power supply
- Magnetic diffuser
- Quick reference guide