

Freedom Par Q12

When your event calls for bright, punchy, battery-operated uplighting, reach for Freedom Par Q12. Add perfectly blended color to any room like an event boss with this fully wireless quad-color uplight. Enjoy flexible control with both built-in D-Fi and a built-in RF receiver. Place inside sticks of TRUSST® for instant truss warming looks. With an easy-to-read full-text OLED display that lets you pick the right dimming curve for your light show—keep your uplighting going all event long!

HIGHLIGHTS

- 100% TRUE wireless, battery-operated, quad-color (RGBA) LED uplight with built-in D-Fi transceiver
- New secondary optics provide perfect color blending with nearly no artifacts
- Magnetic diffuser pops on or off with ease and widens the coverage area
- OLED display allows for full-text and to easily change fixture settings
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- Adjust the projection angle using the spring-loaded kickstand
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Achieve smooth LED fading with built-in dimming curves
- Compact and lightweight design easily fits inside sticks of TRUSST®



SPECIFICATIONS

- DMX Channels : 4, 6, or 14
- DMX Connectors : 3-pin XLR
- Max Unobstructed Distance : 600 ft (183 m)
- Light Source : 12 LEDs (quad-color RGBA) 6W, (1.5 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 12°
- Field Angle : 23°
- Maximum Run Time : up to 7 hours
- Recharge Time : 4 hours
- Operating Frequency : 2.412 to 2.484 GHz
- Illuminance : 4,185 lux @ 2 m
- Lumens : 1,255
- Input Voltage : 24 VDC, 1.5 A (external power supply: 24 VDC, 50/60 Hz)
- Power and Current : 22 W, 0.3 A @ 120 V, 60 Hz
- Weight : 5.4 lbs (2.4 kg)
- Size : 8.7 x 7.8 x 4.8 in (222 x 197 x 123 mm)
- Approvals : CE, RoHS, FCC
- Illuminance (with diffuser) : 1,005 lux @ 2 m
- Maximum Run Time (single color) : up to 9.5 hours
- Startup Temperature : -4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature : -22 °F to 113 °F (-30 °C to 45 °C)
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- Freedom Par Q12
- External power supply
- Magnetic diffuser
- Quick Reference Guide