

# Freedom Par Q9

## HIGHLIGHTS

- 100% TRUE wireless, battery-operated, quad-color (RGBA) LED uplight with built-in D-Fi transceiver
- New secondary optics provide perfect color blending with nearly no artifacts
- Magnetic diffuser pops on or off with ease and widens the coverage area
- Adjustable run times ensure the fixture will last the length of the event
- OLED display allows for full-text and to easily change fixture's settings
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- Adjust the projection angle using the spring-loaded kickstand
- Built-in glare shield protects light spillage and eye fatigue
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Achieve smooth LED fading with built-in dimming curves
- Compact and lightweight design easily fits inside sticks of TRUSST®



## SPECIFICATIONS

- DMX Channels : 4, 6 or 14
- Max Unobstructed Distance : 600 ft (183 m)
- Light Source : 9 LEDs (quad-color RGBA) 6 W, (2.3A), 50,000 hours life expectancy
- Strobe Rate : 0 to 22 Hz
- Beam Angle : 19°
- Field Angle : 35°
- Recharge Time : 3 hours
- Operating Frequency : 2.412 to 2.484 GHz
- Illuminance : 3580 lux @ 2 m
- Lumens : 1,161
- Input Voltage : 24 VDC, 1.5 A (external power supply: 24 VDC, 50/60 Hz)
- Power and Current :
  - 31 W, 0.3 A @ 120 V, 60 Hz
  - 30 W, 0.2 A @ 230 V, 50 Hz
- Weight : 4.6 lbs (2.1 kg)
- Size : 4.7 x 4.7 x 4.9 in (120 x 120 x 126 mm)
- Approvals : CE, UKCA, RoHS, FCC
- Beam Angle (with diffuser) : 37°
- Field Angle (with diffuser) : 68°
- Illuminance (with diffuser) : 529 lux @ 2 m
- Lumens : 1,161
- Run Time (adjustable) : 3, 5, 8, or 12 hrs
- Mounting Hole : M12
- Optional Controllers : RFC, RFC-XL, FlareCON

## WHAT'S INCLUDED

- Freedom Par Q9
- External power supply
- Magnetic Diffuser
- Quick Reference Guide