

Freedom Par T6

HIGHLIGHTS

- 100% TRUE wireless, battery-operated, tri-color (RGB) LED uplight with built-in D-Fi transceiver
- New secondary optics provide perfect color blending with nearly no artifacts
- Magnetic diffuser pops on or off with ease and widens the coverage area
- Adjustable run times ensure the fixture will last the length of the event
- OLED display allows for full-text and to easily change fixture's settings
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- Adjust the projection angle using the spring-loaded kickstand
- Built-in glare shield protects light spillage and eye fatigue
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Achieve smooth LED fading with built-in dimming curves
- Ultra-Compact and lightweight design easily fits inside sticks of TRUSST®



SPECIFICATIONS

- DMX Channels : 3, 5 or 13
- Max Unobstructed Distance : 600 ft (183 m)
- Light Source : 6 LEDs (RGB) 3 W, (0.7 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 27 Hz
- Beam Angle : 13°
- Field Angle : 29°
- Recharge Time : 4 hours
- Operating Frequency : 2.412 to 2.484 GHz
- Illuminance : 1876 lux @ 2 m
- Lumens : 775
- Input Voltage : 24 VDC, 3.5A A (external power supply: 100-230 VAC, 50/60 Hz)
- Power and Current :
 - 35 W, 0.52 A @ 120 V, 60 Hz
 - 35 W, 0.33 A @ 230 V, 50 Hz
- Weight : 2.6 lb. (1.2 kg)
- Size : 3.9 x 3.9 x 5.1 in (98 x 98 x 130 mm)
- Approvals : CE , UKCA , ROHS , FCC
- Run Time (adjustable): : 3, 5, 8, or 12 hrs
- Bracket Mounting Hole : M12
- Optional Controllers : RFC, RFC-XL, FlareCon Air

WHAT'S INCLUDED

- Freedom Par T6
- External power supply
- Magnetic diffuser
- Quick Reference Guide