

# Freedom Strip Mini RGBA

## HIGHLIGHTS

- 100% TRUE wireless, battery-operated RGBA LED strip light with built-in D-Fi™ 2.4 GHz wireless control
- Create rich colors and pastels with amber LEDs
- Master/slave wirelessly using D-Fi 2.4 GHz with other Freedom™ fixtures for a coordinated light show.
- Create coordinated light shows by linking other Freedom™ Par RGBA, Freedom™ Strip Mini and Freedom™
- Par fixtures in master/slave mode
- Convenient wireless control using D-Fi™ 2.4 GHz or IRC remote
- Send and receive wireless DMX signals with the built-in D-Fi™ 2.4 GHz transceiver
- Set up and tear down in a fraction of the time by eliminating the need for DMX or power cables
- Extended run time of up to 20 hours with the rechargeable, lithium-ion battery
- Achieve pristine color mixing with 200 RGBA LEDs (50 red, 50 green, 50 blue and 50 amber)
- Wireless control of sectional, eye-catching chase effects via DMX or IRC remote
- Extend the battery's lifespan with built-in discharge protection
- Shine light where it is needed using the adjustable tilt
- Access built-in, eye-catching automated and sound-activated programs via wireless DMX, IRC remote or master/slave mode
- Functions as a D-Fi™ 2.4 GHz transmitter or receiver to transmit wireless DMX to any D-Fi™ 2.4 GHz receiver fixture including Freedom™ Par and Freedom™ Strip Mini
- IRC remote provides wireless non-DMX control
- Easily connects to Freedom™ Par and Freedom™ Strip Mini using backward compatibility mode
- Enhance light shows with adjustable electronic strobe and dimmer effects
- Easily charge, store and transport your fixtures from gig to gig in the Freedom™ Charge S.



## SPECIFICATIONS

- DMX Channels : 4 or 5
- DMX Connectors : 3-pin XLR
- Light Source : 200 LEDs (50 red, 50 green, 50 blue, 50 amber) 0.25 W (20 mA) 100,000 hours life expectancy
- Beam Angle : 13°
- Field Angle : 24°
- Maximum Run Time : (all on): up to 8 hours  
(single color): up to 20 hours
- Recharge Time : 6 hours
- Operating Frequency : 2.433 to 2.481 GHz
- Illuminance : 1,370 lux @ 2 m
- Power Linking : 16 units @ 120 V; 25 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 71 W, 0.6 A @ 120 V, 60Hz  
94 W, 0.4 A @ 230 V, 50Hz
- Weight : 7.6 lb (3.4 kg)
- Size : 20 x 3 x 8.3 in (510 x 78 x 210 mm)
- Approvals : CE, FCC
- Included Controllers : IRC

## WHAT'S INCLUDED