

GigBAR Move ILS

GigBAR Move ILS is a 5-in-1 pack and play system that controls ILS, our patent-pending lighting technology that expanded the possibilities of impressive light show synchronization quickly and easily. GigBAR Move ILS can control any product in the ILS ecosystem, wired or wirelessly. GigBAR Move ILS has moving heads, derbies, washes, a laser, and strobe effect pre-mounted onto a single bar. Easily control the unit via stand-alone, DMX, wireless RF remote or wireless footswitch so you can get to the good times sooner.

HIGHLIGHTS

- 5-in-1 lighting system that includes moving heads, derbies, washes, a laser and strobe effect pre-mounted on a single bar
- ILS compatibility for use in the ILS ecosystem (ILS) is a complete lighting ecosystem technology that provides an advanced, coordinated light show across multiple fixture types
- Control any ILS-enabled fixture wirelessly with built-in D-Fi transceiver
- Use the included RF remote to trigger the built-in shows without needing line of sight
- Separate color and gobo wheels in moving heads allow for creative programming
- Totem Mode keeps the moving heads focused on the dance floor
- Easy navigation and access to all functions, directly from the full-color LCD display
- Safely mounts to truss or ceilings using the 3/8 in threaded inserts
- System includes a tripod, wireless footswitch, RF remote and FREE carry bags to ensure quick setup
- Built-in UV LEDs illuminate florescent objects and make them pop
- Individual control of each effect ensures your show looks the way you need it to
- Easy control via stand-alone, DMX, wireless RF remote or wireless footswitch



SPECIFICATIONS

- DMX Channels : 3, 27 or 46
- DMX Connectors : 3- pin XLR
- Pan and Tilt : 540°/180°
- Colors : (moving head): 7 + white, continuous scroll at variable speeds
- Gobos : (moving head): 7 + open, continuous scroll at variable speeds
- Light Source :
 - (pars): 3 LEDs (quad-color RGB+UV) 3.5 W (1 A), 50,000 hours life expectancy
 - (strobe): 4 LEDs (white & UV) 5 W (1 A), 50,000 hours life expectancy
 - (derby): 6 LEDs (2 red, 2 green, 2 blue) 1 W (1 A), 50,000 hours life expectancy
 - (moving head): 1 LED (cool white) 10 W (2.3 A), 50,000 hours life expectancy
 - (laser): 650nm/100 mW (red) laser diode, 532 nm/30 mW (green) laser diode
- Strobe Rate : 0 to 20 Hz
- Beam Angle : (moving head): 11°
 - (pars): 19°
 - (strobe): 8°
- Field Angle : (pars): 30°
 - (strobe): 18°
- Coverage Angle : (derby): 131°
 - (laser): 93°
- Fits Tripod Size : 1.5 in (37.4 mm)
- Illuminance :
 - (pars): 1,205 lux @ 2 m (per par)
 - (moving head): 1056 lux @ 2 m (per head)
 - (strobe): 86 lux @ 2 m (per LED)
- Power Linking : 7 units @ 120 V; 12 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
 - 81 W, 1.1 A @ 120 V, 60 Hz
 - 79 W, 0.6 A @ 230 V, 50 Hz
- Weight : 23.4 lb (10.7 kg)
- Size : 43 x 5.7 x 17.7 in (1100 x 144 x 449 mm)
- Approvals : CE, RoHS, UKCA, FDA, FCC
- Stand Height : 4.8 ft to 8.3 ft (1.5 to 2.5 m)
- Tripod leg width : 3.9 ft (1.2 m)
- Footswitch Operating Frequency : 433 MHz

- Foot Switch Max Unobstructed Distance : 100 ft (30.5 m)
- Footswitch battery : 9 V alkaline
- Included Controllers : RF remote, wireless footswitch

WHAT'S INCLUDED

- GigBAR Move ILS
- Power cord
- Carrying bag
- Tripod
- Footswitch
- RF Remote
- Quick Reference Guide
- Key and interlock (EU)