


GigBAR Move + ILS

HIGHLIGHTS

- 5-in-1 lighting system that includes moving heads, derbies, washes, a laser and strobe effect pre-mounted on a single bar
- ILS compatibility for use in the ILS ecosystem (ILS) is a complete lighting ecosystem technology that provides an advanced, coordinated light show across multiple fixture types
- Control any ILS-enabled fixture wirelessly with built-in D-Fi transceiver
- Use the included RF remote to trigger the built-in shows without needing line of sight
- Powerful moving heads with separate color and gobo wheels allow for creative programming
- Totem Mode keeps the moving heads focused on the dance floor
- Easy navigation and access to all moving head functions directly from the full-color LCD display
- Safely mounts to truss or ceilings using the 3/8 in threaded inserts
- System includes a tripod, wireless footswitch, RF remote and FREE carry bags to ensure quick setup
- Built-in UV LEDs illuminate florescent objects for dazzling blacklight effects
- Individual control of each effect ensures your show looks the way you need it to
- Easy control via stand-alone, DMX, wireless RF remote or wireless footswitch



SPECIFICATIONS

- DMX Channels : 3, 29, or 51
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/180°
- Colors :
(moving head): 9 + open, split colors, continuous scroll at variable speeds
- Gobos :
(moving head): 9 + open, continuous scroll at variable speeds
- Light Source :
(pars): 3 LEDs (hex color RGBAW+UV) 6 W (2 A), 50,000 hours life expectancy
(strobe): 4 LEDs (cool white) 5 W (1.2 A), 50,000 hours life expectancy
(derby): 8 LEDs (2 red, 2 green, 2 blue, 2 white) 6.5 W (2 A), 50,000 hours life expectancy
(moving head) 1 LED (cool white) 32 W, (3 A), 50,000 hours life expectancy
(Laser) 638 nm/30mW (red) laser diode, 520 nm/20 mW (green) laser diode, 450 nm/ 50 mW (blue) laser diode
- Strobe Rate : 0 to 30 Hz
- Beam Angle :
(moving head): 17°
(pars): 22°
(strobe): 30°
- Field Angle :
(pars): 33°
(strobe): 62°
- Coverage Angle :
(derby): 131°
(laser): 93°
- Fits Tripod Size : 1.5 in (37.4 mm)
- Illuminance :
(pars): 1,205 lux @ 2 m (per par)
(moving head): 5,140 lux @ 2 m (per head)

- (strobe): 130 lux @ 2 m
- Power Linking : 7 units @ 120 V; 12 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
250 W, 3 A @ 120 V, 60 Hz
248 W, 1.8 A @ 230 V, 50 Hz
- Weight : (bar only) 31 lbs (14 kg)
- Size : 43 x 5.7 x 17.7 in (1100 x 144 x 449 mm)
- Approvals : CE, UKCA, RoHS, FCC, FDA
- Stand Height : 4.8 ft to 8.3 ft (1.5 to 2.5 m)
- Footswitch Operating Frequency : 433 MHz
- Footswitch Max Unobstructed Distance : 100 ft (30.5 m)
- Max Unobstructed Distance (D-Fi) : 600 ft (183 m)
- Footswitch Battery : 9 V alkaline
- Included Controllers : RF remote, wireless footswitch
- Cable Length : 10 ft (3 m)
- Tripod Thickness : 1.37 in (35 mm)
- Optional Controllers : RF
- RF Remote Battery : 23A, 12 V alkaline
- Complies with FDA performance standards for laser products except for deviations pursuant to Laser Notice No. 56, dated May 8, 2019 :

WHAT'S INCLUDED

- GigBar Move Plus ILS
- Power cord
- RF Remote
- Carry bag
- Tripod
- Tripod carry bag
- Footswitch
- User Manual