ILS Command

HIGHLIGHTS

- Powerful ILS controller capable of programing any ILSenabled product
- Built-in D-Fi transmitter controls an unlimited number of ILSenabled fixtures
- Customize, save and recall presets without using DMX
- Backlit silicon buttons provide a tactile response in dark environments
- Innovative follow spot mode highlights grand entrances
- without interrupting the rest of the show
 Backup, restore and update the controller's software using the built-in USB port
- Ensure unauthorized access is blocked by enabling the onboard lockout
- Built-in audio connector allows for better accuracy when triggering lights to the beat
- Manually override the show on the fly using the 9 guick color access buttons
- Safely transport the controller with the included carry case



SPECIFICATIONS

- Max Unobstructed Distance : 600 ft (183 m) Operating Frequency : 2.412 to 2.484 GHz
- Weight: 3.6 lb (1.6 kg)
 Size: 12.3 x 9.9 x 0.7 in (313 x 252 x 19 mm)
 Approvals: CE, UKCA, RoHS, FCC
 ILS Connectors: 3-pin XLR

- Programmable Presets: 6
- Cable Length: 20 in (508 mm) Input Voltage (USB-C): 5V, 1A

WHAT'S INCLUDED

- **ILS Command**
- External power supply
- USB-C cable
- Carry bag Quick Reference Guide

