ILS Command

HIGHLIGHTS

- Powerful ILS controller capable of programing any ILS-enabled product
- Built-in D-Fi transmitter controls an unlimited number of ILSenabled fixtures
- Customize, save and recall presets without using DMX
- Backlit silicon buttons provide a tactile response in dark environments
- Innovative follow spot mode highlights grand entrances without interrupting the rest of the show
- Backup, restore and update the controller's software using the built-in USB port
- Ensure unauthorized access is blocked by enabling the onboard lockout
- Built-in audio connector allows for better accuracy when triggering lights to the beat
- Manually override the show on the fly using the 9 quick color access buttons
- Safely transport the controller with the included carry case



SPECIFICATIONS

Max Unobstructed Distance: 600 ft (183 m)
Operating Frequency: 2.412 to 2.484 GHz

Weight: 3.6 lb (1.6 kg)

• Size: 12.3 x 9.9 x 0.7 in (313 x 252 x 19 mm)

Approvals: CE, UKCA, RoHS, FCC
 ILS Connectors: 3-pin XLR
 Programmable Presets: 6
 Cable Length: 20 in (508 mm)
 Input Voltage (USB-C): 5V, 1A

WHAT'S INCLUDED

ILS Command

External power supply

USB-C cable

Carry bag

• Quick Reference Guide

