## Intimidator Barrel LED 300

## HIGHLIGHTS

- Bright and compact LED barrel scanner packed with features to enhance any show
- Increase design flexibility and effects with interchangeable, rotating gobos plus separate, saturated colors
- Minimize programming time with built-in movement macros and move-in-black features
- Project crisp gobos from nearly any distance using the motorized focus
- Increase effects with electronic dimming and strobe features
- Split the beam and cover larger areas with the crisp, 3-facet prism
  Continuous shows with individual reset of pan and tilt, color, gobo,
- Commodes shows with manual reset of part and till, color, good prism and focus
   Applique flicker free video operation with high frequency LED.
- Achieve flicker-free video operation with high-frequency LED dimming
- Save time running cables and extension cords by power linking multiple units (US version only)
- Sound-activated programs dance to the beat of the music
- Generate a synchronized show in master/slave mode using easyaccess to built-in automated programs

## **SPECIFICATIONS**

- DMX Channels : 8 or 11
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 180°/360°
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open, rotating, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (white) 60 W (15 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Illuminance : 1,736 lux @ 2 m
- Power Linking : 3 units @ 120 V; 7 units @ 230 V
- Input Voltage : 120/230 VAC, 50/60 Hz (switchable)
- Power and Current : 240 W, 2 A @ 120 V, 60 Hz
- 240 W, 1 A @ 230 V, 50 Hz
- Gobo Size : 23.8 mm outside, 20.9 mm image, 2 mm max thickness
- Weight : 14.2 lb (6.4 kg)
- Dimensions : 20.5 x 10 x 6.7 in (521 x 255 x 171 mm)
- Approvals : CE, MET



