

# Intimidator Beam 355 IRC

## HIGHLIGHTS

- Feature-packed moving head beam fitted with a 100W LED
- Motorized frost filter converts the beam to a wash
- Easily generate complex looks using the fixed gobo wheel plus animation effect
- Split the beam and cover larger areas with the rotating 3-facet prism
- Full-color display with IRC-6 compatibility, totem mode and onboard memory for storing a scene
- Unique ¼-turn hanging bracket allows for single or dual clamp mounting options
- powerCON®-compatible power input/output connections for power linking
- Fits best in the INTIMROADCASES35X flight case



## SPECIFICATIONS

- DMX Channels : 8 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 180°, 360°, 540° pan/270°, 180°, 90° tilt
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 5 + open, animation effect, continuous scroll at variable speeds
- Light Source : 1 LED (white) 100 W, (27 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- PWM Frequency : 1.8 kHz [flicker free]
- Beam Angle : 3°
- Illuminance : 262,800 lux @ 2 m  
6,860 lux @ 5 m
- Power Linking : 5 units @ 120 V; 9 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 163 W, 1.5 A @ 120 V, 60 Hz  
157 W, 0.8 A @ 230 V, 50 Hz
- Weight : 25.4 lb (11.6 kg)
- Size : 12.7 x 8.7 x 18.9 in (322 x 220 x 480 mm)
- Approvals : CE, MET
- Optional Controllers : IRC - 6
- Prism : 3-facet round, bidirectional rotation at variable speeds

## WHAT'S INCLUDED

- Intimidator Beam 355 IRC
- Power cord
- Hanging bracket
- Warranty card
- Quick Reference Guide