Intimidator Hybrid 140SR

HIGHLIGHTS

- True hybrid moving head fitted with an intense 140 W discharge light engine
- All-in-one light fixture morphs from SPOT to BEAM to WASH effortlessly
- Dual, overlapping prisms with independent control multiply the beam dynamics
- Dual gobo wheels allow for gobo morphing and amazing mid-air projections
- Motorized zoom works in beam, spot and wash modes for ultimate light control
- Unique ¼-turn hanging bracket allows for single or dual clamp mounting options
- Emit crisp projections at almost any distance using the motorized focus
- · Glass optics ensure crisp beams and gobos at all times
- Flexible menu option accepts Osram 132 W lamps if needed
- Full-color display with IRC-6 compatibility, totem mode and onboard memory for storing a scene
- powerCON®-compatible power input/output connections for power linking
- Fits best in the Intimidator Road Case S35X



SPECIFICATIONS

DMX Channels: 13 or 19
DMX Connectors: 3-pin XLR

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt
Colors: 12 + white, split colors, continuous scroll at variable speeds

 Light Source: (included): Osram Sirius HRI 140 W discharge lamp (6,000 hrs) (optional): Osram Sirius HRI 132 W discharge lamp (6,000 hrs)

Strobe Rate: 0 to 20 Hz

• Illuminance : (3° beam): 382,000 lux @ 5 m

(7° spot): 104,700 lux @ 5 m (14° wash): 4,680 lux @ 5 m

Power Linking: 3 units @ 120 V; 6 units @ 230 V

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

 Power and Current: 260 W, 2.5 A @ 120 V, 60 Hz 254 W, 1.3 A @ 230 V, 50 Hz

Zoom Angle : (beam): 3° to 11°

(spot): 7° to 21° (wash): 14° to 28° Weight: 33.4 lb (15.2 kg)

Size: 12.6 x 8.6 x 20.2 in (322 x 220 x 513 mm)

Approvals : CE, METOptional Controllers : IRC - 6

Prism: (1): 8-facet round, bidirectional rotation at variable speeds
(2): 6-facet linear, bidirectional rotation at variable speeds

- Gobo wheel (1): 9 + open, rotating, indexing, interchangeable, slot-n-lock, continuous scroll at variable speeds
- Gobo wheel (2): 17 + open, aluminum, continuous scroll at variable speeds
- Gobo Size (rotating): 13.7 mm outside, 11 mm image, 1 mm max thickness

WHAT'S INCLUDED

Intimidator Hybrid 140SR



- Power cord
- Hanging bracket
- Warranty card
- Quick Reference Guide

