Intimidator Scan 360

HIGHLIGHTS

- Feature-packed scanner fitted with a 100 W LED designed for mobile performances
- Project crisp gobos from nearly any distance with the motorized focus
- Split the beam and cover larger areas with the crisp, 3-facet rotating prism
- Convenient, wireless non-DMX control using the optional IRC-6 remote
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Achieve flicker-free video operation with high-frequency LED dimming
- Save time running cables and extension cords by power linking multiple units



SPECIFICATIONS

DMX Channels: 8 or 12
DMX Connectors: 3-pin XLR
Pan and Tilt: 172°/39°

• Colors: 8 + white, split colors, continuous scroll at variable speeds

Gobos: 7 + open (6 metal, 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

Light Source: 1 LED (white) 100 W, (4.2 A), 50,000 hours life expectancy

• Strobe Rate : 0 to 20 Hz

Beam Angle : 21°

Illuminance: 4,050 lux @ 2 m

Power Linking: 4 units @ 120 V; 7 units @ 230 V

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current : 147 W, 1.9 A @ 120 V, 60 Hz

• Gobo Size : Gobo Size (metal): 19.75 mm outside, 14mm image, 1 mm max thickness

• Weight: 12.6 lb (5.7 kg)

Size: 10 x 6.1 x 16.3 in (255 x 155 x 415 mm)

Approvals : CE

Prism: 3-facet round, rotation at variable speeds
 Power and Current: 143 W, 1.1 A @ 230 V, 50 Hz

Optional Controllers : IRC

WHAT'S INCLUDED

Power cord

Quick Reference Guide

