

# Intimidator Scan LED 300

## HIGHLIGHTS

- Bright, and compact LED scanner packed with features to enhance any show
- Increase design flexibility and effects with interchangeable, rotating gobos plus separate, saturated colors
- Minimize programming time with built-in movement macros and move-in-black features
- Project crisp gobo from nearly any distance with the motorized focus
- Increase effects with electronic dimming and strobe features
- Split the beam and cover larger areas with the crisp, 3-facet prism
- Continuous shows with individual reset of pan/tilt, color, gobo, prism
- Achieve flicker-free video operation with high-frequency LED dimming
- Save time running cables and extension cords by power linking multiple units (US version only)
- Sound-activated programs dance to the beat of the music
- Generate a synchronized show in master/slave mode with easy-to-access, built-in automated programs



## SPECIFICATIONS

- DMX Channels : 8 or 11
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 180°/90°
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (5 metal + 2 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (white) 60 W (14.9 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 21°
- Illuminance : 2,850 lux @ 2 m
- Power Linking : 3 units @ 120 V; 7 units @ 230 V
- Input Voltage : 120/230 VAC, 50/60 Hz (switchable)
- Power and Current : 236 W, 2 A @ 120 V, 60 Hz  
237 W, 1 A @ 230 V, 50 Hz
- Gobo Size : 23.8 mm outside, 20.9 mm image, 2 mm max thickness
- Weight : 14.7 lb (6.7 kg)
- Dimensions : 11 x 10 x 18.9 in (279 x 254 x 478 mm)
- Approvals : CE, MET

## WHAT'S INCLUDED