

Intimidator Spot 400 IRC

HIGHLIGHTS

- Exceptionally bright, 140-W LED moving head spot designed for large events
- Simple navigation and full text readout with the high-contrast, full color LCD display
- Power link multiple units to save time running extension cords
- Easy-access gobo door allows for quick gobo changes without opening the fixture
- Emit crisp projections at almost any distance using the motorized focus
- 3-facet rotating prism splits the beam for great effects and to cover a larger area
- Built-in effect macros and move-in-black feature minimizes programming time
- Activate built-in, automated and sound-activated programs, or control in DMX or Master/Slave mode
- Project light where you want it with user-selectable pan and tilt ranges
- Continuous shows with individual reset of pan/tilt, color, gobo, prism and focus
- Fits best in the CHS-50 VIP Gear Bag
- Works with the optional IRC-6 for wireless control and triggering
- Compact housing is light and easy to transport between shows



SPECIFICATIONS

- DMX Channels : 8 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors : 7 + white, split colors, continuous scroll at variable speeds
- Gobos : 8 + open (7 metal + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (white) 140 W (2.9 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 22 Hz
- PWM Frequency : 733 Hz
- Beam Angle : 18°
- Illuminance : 11,440 lux @ 2 m
- Power Linking : 5 units @ 120 V; 10 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 273 W, 2.3 A @ 120 V, 60 Hz
244 W, 1.2 A @ 230 V, 50 Hz
- Gobo Size : 26.7 mm outside, 23 mm image, 1 mm max thickness
- Weight : 38.8 lb (14.4 kg)
- Size : 9.7 x 13.4 x 18.5 in (248 x 340 x 470 mm)
- Approvals : CE
- Optional Controllers : IRC-6

WHAT'S INCLUDED