

# Intimidator Spot 455Z IRC

## HIGHLIGHTS

- Extremely bright, 180 W LED moving head spot designed for large events
- Dual gobo wheels allow for gobo morphing and amazing mid-air projections
- Motorized zoom for short- or long-throw situations
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Split the beam and cover a larger area with the 3-facet prism
- Emit crisp projections at almost any distance using the motorized focus
- Quickly and easily change gobos using the easy-access gobo door
- Convenient, wireless non-DMX control using the optional IRC-6 remote
- Set, save, and recall 1 scene manually directly from the full-color LCD display
- Save time running cables by power linking multiple units
- Fits best in the CHS-50 VIP Gear Bag



## SPECIFICATIONS

- DMX Channels : 10 or 16
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/240°
- Pan and Tilt Ranges : 180°, 360°, 540° pan/90°, 180°, 240° tilt
- Colors : 7 + white, split colors, continuous scroll at variable speeds
- Gobos : wheel (1): 7 + open (6 aluminum + 1 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable speeds  
wheel (2): 8 + open (8 stamped), continuous scroll at variable speeds
- Light Source : 1 LED (white) 180 W (48.1 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 15 Hz
- PWM Frequency : 1,000 Hz
- Illuminance : (13°): 38,200 @ 2 m  
(28°): 8,720 lux @ 2 m  
(13°) 7,700 lux @ 5 m (28°) 1,650 lux @ 5 m
- Power Linking : 2 units @ 120 V; 5 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 327 W, 2.9 A @ 120 V, 60 Hz  
304 W, 1.5 A @ 230 V, 50 Hz
- Gobo Size : (rotating): 25.9 mm outside, 21 mm image, 1 mm max thickness
- Zoom Angle : 13° to 28°
- Weight : 42.2 lb (19.2 kg)
- Size : 16.6 x 11.9 x 20.5 in (423 x 303 x 520 mm)
- Approvals : CE
- Optional Controllers : IRC-6
- Prism : 3-facet round, bidirectional rotation at variable speeds

## WHAT'S INCLUDED

- Power cord
- Hanging bracket with mounting hardware
- Warranty card
- Quick Reference Guide