Intimidator Spot 475Z

HIGHLIGHTS

- Extremely bright, 250 W LED moving head spot designed for large events
- Dual rotating prisms split the beam for great effects and cover a larger area
- Dual gobo wheels allow for gobo morphing and amazing mid-air projections
- Motorized zoom for short- or long-throw situations
- Unique ¼-turn hanging bracket allows for single or dual clamp mounting options
- Emit crisp projections at almost any distance using the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Convenient, wireless non-DMX control using the optional IRC-6 remote
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- powerCON®-compatible power input/output connections for power linking



SPECIFICATIONS

DMX Channels: 10 or 16DMX Connectors: 3-pin XLR

Pan and Tilt : 540°/270°

• Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt

• Colors: 7 + white, split colors, continuous scroll at variable speeds

Gobos: (1): 7 + open (6 metal + 1 glass), rotating, interchangeable, indexing, continuous scroll at variable speeds
(2): 8 + open, continuous scroll at variable speeds

• Light Source: 1 LED (white) 250 W, (16.3 A), 50,000 hours life expectancy

Strobe Rate: 0 to 20 HzPWM Frequency: 2 kHz

Illuminance : (13°): 106,300 lux @ 2 m

(28°): 23,680 lux @ 2 m (13°): 14,290 lux @ 5 m (28°): 3,741 lux @ 5 m

Lumens: 10,433

Power Linking: 3 units @ 120 V; 5 units @ 230 V

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

 Power and Current: 380 W, 3.4 A @ 120 V, 60 Hz 378 W. 1.9 A @ 230 V. 50 Hz

Gobo Size: 25.7 mm outside, 21 mm image, 1.3 mm max thickness

• Zoom Angle : (motorized): 13° to 28°

Weight: 36.2 lb (16.5 kg)

Size: 14.3 x 9.8 x 20.9 in (363 x 250 x 531 mm)

Approvals : CE, MET

Prism: (1): 6-facet round, bidirectional rotation at variable speeds
(2): 6-facet linear, bidirectional rotation at variable speeds

Optional Controllers : IRC-6

WHAT'S INCLUDED

- Intimidator Spot 475Z
- Power cord
- · Hanging bracket



4000 K CTO filter

