

Intimidator Spot 60 ILS

HIGHLIGHTS

- Feature-packed moving head designed for mobile performances
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB® compatibility for wireless Master/Slave or DMX control
- New home position allows for smoother programming
- ¼-turn hanging bracket allows for quick removal when needed
- Project crisp gobos from nearly any distance with the motorized focus
- Manual zoom for short or long throw applications
- 3-facet prism splits the beam and covers a larger area
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Link up to 4 fixtures to create eye-catching, synchronized shows in Automated or Sound mode



SPECIFICATIONS

- DMX Channels : 8, 10 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/240°
- Pan and Tilt Ranges : 180°, 360°, 540° pan/90°, 180°, 240° tilt.
- Colors : 8 + open, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 metal + 1 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (cool white) 70 W, (3.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Illuminance :
(15°) : 10,012 lux @ 2 m
(17°) : 7,792 lux @ 2 m
- Power Linking : 5 units @ 120 V; 9 units @ 230 V
- Input Voltage :
100 to 240 VAC
50/60 Hz (auto-ranging)
- Power and Current :
107 W, 1.5 A @ 120 V, 60 Hz
105 W, 1 A @ 230 V, 50 Hz
- Gobo Size : 24 mm outside, 20 mm image, 1.1 mm max thickness
- Zoom Angle : (manual) 15° to 17°
- Weight : 11.2 lb (5.1 kg)
- Size : 9.9 x 7.8 x 13.8 in (251 x 199 x 351mm)
- Approvals : CE, RoHS, UKCA
- Prism : 3-facet round static
- Optional Controllers : IRC-6
- Color Temperature : 15,000 K
- Bracket Mounting Hole : 13 mm

WHAT'S INCLUDED

- Intimidator Spot 60 ILS
- Power cord
- Omega bracket
- Quick Reference Guide

