Intimidator Spot LED 350 X2

HIGHLIGHTS

- Feature-packed, moving head spot fitted with a 75 W LED
- Project crisp gobos from nearly any distance with the motorized
- Split the beam and cover a larger area using the 3-facet rotating
- Suitable for every event with either black or white housings
- Quickly and easily change gobos using the easy-access gobo door
- Achieve super-smooth LED fading with the built-in, electronic
- Throw light farther by decreasing the beam angle by 5° using the manual zoom
- Project light where you want it with user-selectable pan and tilt
- Minimize programming time with built-in effect macros and movein-black feature
- Save time running cables and extension cords by power linking
- Continuous shows with individual reset of pan/tilt, color, gobo, prism and focus
- Sound-activated programs dance to the beat of the music
- Generate a synchronized show in Master/Slave mode with easy-toaccess, built-in automated programs
- Fits best in the CHS-50 VIP Gear Bag



SPECIFICATIONS

DMX Channels: 8 or 14 DMX Connectors: 3-pin XLR

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt Colors: 8 + white, split colors, continuous scroll at variable speeds

Gobos: 7 + open, rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

Light Source: 1 LED (white) 75 W (17 A), 50,000 hours life expectancy

Strobe Rate: 0 to 20 Hz

Illuminance: (12°): 9,490 lux @ 2 m

(17°): 4,670 lux @ 2 m

Power Linking: 3 units @ 120 V; 7 units @ 230 V

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 272 W, 2.2 A @ 120 V, 60 Hz 285 W, 1.2 A @ 230 V, 50 Hz

Gobo Size: 24 mm outside, 20 mm image, 1.1 mm max thickness

Zoom Angle: (manual): 12° to 17°

Weight: 22.7 lb (10.3 kg)

Size: 10.6 x 13.4 x 15.4 in (268 x 340 x 392 mm)

Approvals: CE

WHAT'S INCLUDED

